

INDUSTRIAL COMPONENT DATA

NHI-E-10-PKZ0-PI 199327 Y7-199327 EATON ELECTRIC

NHI-E-10-PKZ0-PI

Brand: EATON - MOELLER | Manufacturer Part Number: NHI-E-10-PKZ0-PI



Manufacturer	EATON - MOELLER
MPN / Reference	NHI-E-10-PKZ0-PI
Catalog number	Y7-199327
Category	Auxiliary contact block
Minimum order	5 Pcs
Document ID	EO-EA16A22774
Generated	2026-08-05

Product Overview

NHI-E-10-PKZ0-PI

Eaton Moeller® series NHI Standard auxiliary contact, NHI-E, 1 N/O, Can be fitted to the front, Push in terminals
Standard auxiliary contact, Contacts N/O = Normally open: 1 N/O, For use with: DILM

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > Circuit Breakers PKZ**

Additional Product Information

General specifications

Product Name Eaton Moeller® series NHI Accessory Standard auxiliary contact Catalog Number 199327 Model Code NHI-E-10-PKZ0-PI EAN 4015081974115 Product Length/Depth 35 mm Product Height 15 mm Product Width 45 mm

Product Weight 0.008 kg Compliances RoHS conform

CE Marked Certifications CSA File No.: 165628

CSA Class No.: 3211-05

UL File No.: E36332

UL Category Control No.: NLRV

UL 508

CE marking

CSA-C22.2 No. 14

IEC 60947-4-1

UL

CSA Features & Functions

Electric connection type Spring clamp connection Features Interlocked opposing contacts General Lifespan, electrical 50,000 Operations Lifespan, mechanical 100,000 Operations Model Top mounting Mounting method Front fastening Overvoltage category III Pollution degree 3 Rated impulse withstand voltage (Uimp) 4000 V AC Used with Motor protective circuit-breaker Climatic environmental conditions Ambient operating temperature - min -25 °C Ambient operating temperature - max 55 °C Terminal capacities Terminal capacity (flexible with ferrule) 1 x (0.5 - 1) mm², auxiliary terminals 2 x (0.5 - 1) mm², auxiliary terminals Terminal capacity (flexible) 2 x (0.5 - 1.5) mm² 0.5 - 1.5 mm² Terminal capacity (solid) 0.5 - 1.5 mm² Terminal capacity (solid/stranded AWG) 20 - 14 Electrical rating Rated operational current (Ie) at AC-15, 220 V, 230 V, 240 V 0.5 A Rated operational current (Ie) at DC-13, 24 V 1 A Rated operational voltage (Ue) at AC - max 440 V Rated operational voltage (Ue) at DC - max 250 V Safe isolation....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / NHI-E-10-PKZ0-PI with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.