

INDUSTRIAL COMPONENT DATA

NHI11-PKZ0-PI 199328 Y7-199328 EATON ELECTRIC NHI11-PKZ0-PI

Brand: EATON - MOELLER | Manufacturer Part Number: NHI11-PKZ0-PI



Manufacturer	EATON - MOELLER
MPN / Reference	NHI11-PKZ0-PI
Catalog number	Y7-199328
Category	Auxiliary contact block
Minimum order	5 Pcs
Document ID	EO-14BA31813D
Generated	2026-08-06

Product Overview

NHI11-PKZ0-PI

Eaton Moeller® series NHI Accessory Standard auxiliary contact, 1 N/O, 1 N/C, Side mounting, Push in terminals

Standard auxiliary contact, Contacts N/O = Normally open: 1 N/O, Contacts N/C = Normally closed: 1 NC, For use with: PKZM01, PKZM0, PKZM4, PKZM0-T, PKM0, PKE

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Circuit Breakers PKZ

Additional Product Information

General specifications

Product Name Eaton Moeller® series NHI Accessory Standard auxiliary contact Catalog Number 199328 Model Code NHI11-PKZ0-PI EAN 4015081974122 Product Length/Depth 68 mm Product Height 92 mm Product Width 15 mm Product Weight 0.044 kg Compliances CE Marked

RoHS conform Certifications CSA File No.: 165628

CSA Class No.: 3211-05

UL File No.: E36332

UL Category Control No.: NLRV

UL 508

CE marking

CSA-C22.2 No. 14

IEC 60947-4-1

UL

CSA Features & Functions

Electric connection type Spring clamp connection Features Interlocked opposing contacts General

Lifespan, electrical 50,000 Operations Model Top mounting Mounting method Side mounting Overvoltage category III

Pollution degree 3 Rated impulse withstand voltage (Uimp) 6000 V AC Used with Motor protective circuit-breaker Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 55 °C Terminal capacities

Terminal capacity (flexible with ferrule) 2 x (0.5 - 1.5) mm², ferrules to DIN 462281 x (0.5 - 1.5) mm², ferrules to DIN 46228 Terminal capacity (flexible) 2 x (0.5 - 2.5) mm²1 x (0.5 - 2.5) mm² Terminal capacity (solid) 2 x (0.5 - 2.5) mm², Control circuit cables1 x (0.5 - 0.25) mm² Terminal capacity (solid/stranded AWG) 20 - 14 Electrical rating

Rated operational current (Ie) 1 A at AC-15, 440 V 500 V Rated operational current (Ie) at AC-15, 220 V, 230 V, 240 V 3.5 A

Rated operational current (Ie) at AC-15, 380 V, 400 V, 415 V 2 A Rated operational cur...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / NHI11-PKZ0-PI with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten PI #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.