

INDUSTRIAL COMPONENT DATA

NHW-SLS-1 179756 Y7-179756 EATON ELECTRIC NH-fuse switch disconnecter,Gr1

Brand: EATON - MOELLER | Manufacturer Part Number: NHW-SLS-1



Manufacturer	EATON - MOELLER
MPN / Reference	NHW-SLS-1
Catalog number	Y7-179756
Category	In-line fuse base
Minimum order	1 Pcs
Document ID	EO-E2C1C2C139
Generated	2026-08-06

Product Overview

NH-fuse switch disconnecter,Gr1

Eaton Distribution parts. 3 pole NH strip-type fuse-switch disconnecter, size NH1, 250A, any feeder unit

Three-pole NH strip-type fuse-switch disconnecter without fuse monitoring; size NH1; supplied without NH fuse-links; vertical mounting position possible; the device is universally suitable for top/bottom cable outgoers; corresponds to 60947-1:2007 + A1:2010 and IEC 60947-3:2008 + A1:2012

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Connection Accessories for Enclosures

Additional Product Information

General specifications

Product Name Eaton Distribution parts Catalog Number 179756 Model Code NHW-SLS-1 EAN 4015081748723 Product Length/Depth 860 mm Product Height 212 mm Product Width 122 mm Product Weight 4.99 kg Compliances RoHS conform Product specifications

Features Double interrupting Number of Poles Three-pole Rated operating voltage (Ue) at AC - max 1000 V Rated uninterrupted current (Iu) 250 A Construction size (fuse inserts) NH1 Electrical connection type of main circuit Rail connection Release indication None Rated conditional short-circuit current (Iq) 80 kA Distance between rail centers 185 mm Model Protection switch separator

ETIM for 179756 Low-voltage industrial controls and switchgear (EC001046)

Feature Name

Feature Value

Model (EF000010)
Protection switch separator
Double interrupting (EF007103)
Yes
Rated permanent current I_u (EF001389)
250 A
Distance between rail centre, 40 mm (EF001431)
No
Distance between rail centre, 50 mm (EF001430)
No
Distance between rail centre, 60 mm (EF001432)
No
Distance between rail centre, 100 mm (EF006048)
No
Distance between rail centre, 185 mm (EF006049)
Yes
Max. rated operation voltage U_e AC (EF007355)
1000 V
Conditioned rated short-circuit current I_q (EF001444)
80 kA
Type of electrical connection of main circuit (EF006819)
Rail connection
Number of poles (EF001391)
3
Construction size fuse insert (EF001452)
NH1
Release indication (EF011943)
None

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / NHW-SLS-1 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.