

## INDUSTRIAL COMPONENT DATA

# NO REPLACEMENT "15KV 15AMP LINK" 15XAB15 EATON ELECTRIC Cartridge fuse, expulsion, MT, 15 A, AC 15 kV, 533 m..

Brand: EATON - MOELLER | Manufacturer Part Number: NO REPLACEMENT "15KV 15AMP LINK"



|                 |                                     |
|-----------------|-------------------------------------|
| Manufacturer    | EATON - MOELLER                     |
| MPN / Reference | NO REPLACEMENT "15KV 15AMP LINK"    |
| Catalog number  | 15XAB15                             |
| Category        | Expulsion fuse-link, medium voltage |
| Minimum order   | 25 Pcs                              |
| Document ID     | EO-DC6917FFDF                       |
| Generated       | 2026-08-06                          |

## Product Overview

Cartridge fuse, expulsion, MT, 15 A, AC 15 kV, 533 mm, ANSI, XA extra rapid  
Ejection Fuse Cartridge, MT, 15 A, AC 15 kV, 533 mm, ANSI, XA extra rapid  
15XAB15 - Expulsion fuse-link, medium voltage, 15 A, AC 15 kV, 533 mm, ANSI, XA extra rapid, style B termination  
Fuse, Expulsion fuse-link, medium voltage, 15 A, AC 15 kV, 533 mm, ANSI, XA extra rapid, fixed NEMA button head link,  
protection of transformer primary side, feeder, capacitor bank, ANSI C37-42, Breaking Capacity 8 kA

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                                  |
|--------------|----------------------------------|
| Catalog path | EATON - MOELLER > Bussmann fuses |
|--------------|----------------------------------|

## Additional Product Information

Expulsion fuse-link, medium voltage, 15 A, AC 15 kV, 533 mm, ANSI, XA extra rapid, style B termination Fuse, Expulsion  
fuse-link, medium voltage, 15 A, AC 15 kV, 533 mm, ANSI, XA extra rapid, fixed NEMA button head link, protection of  
transformer primary side, feeder, capacitor bank, ANSI C37-42, Breaking Capacity 8 kA Delivery program  
Product range Fuse Basic function Expulsion fuse-link Field of application medium voltage Rated current [I] 15 A Rated  
voltage AC 15 kV Size 533 mm Description fixed NEMA button head link Breaking Capacity 8 kA usable for  
size/applications protection of transformer primary side, feeder, capacitor bank Release characteristic [class] XA extra rapid  
Standard/Approval ANSI Standards/Regulations ANSI C37-42  
ETIM for 15XAB15 Circuit breakers and fuses (EC003611)  
Feature Name

**Feature Value**

Rated current (EF000227)

15 A

Rated voltage (EF000228)

15 kV

Voltage type (EF000187)

AC

Rated frequency (EF001663)

50 Hz

Release characteristic (EF000889)

Other

Type of termination (EF012540)

Fixed buttonhead

Standard (EF009322)

ANSI

**REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW**

Send EATON - MOELLER / NO REPLACEMENT "15KV 15AMP LINK" with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

**GLOBAL OFFICES**

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.