

INDUSTRIAL COMPONENT DATA

NOT STAND SPECIAL ORDER 25FE EATON ELECTRIC

Fuse-link, high speed, 25 A, AC 690 V, DC 500 V, BS88, 19 x 77 m..

Brand: EATON - MOELLER | Manufacturer Part Number: NOT STAND - SPECIAL ORDER



Manufacturer	EATON - MOELLER
MPN / Reference	NOT STAND - SPECIAL ORDER
Catalog number	25FE
Category	HRC fuse
Minimum order	10 Pcs
Document ID	EO-A4C179636D
Generated	2026-08-06

Product Overview

Fuse-link, high speed, 25 A, AC 690 V, DC 500 V, BS88, 19 x 77 mm, aR, BS,
NOT STAND - SPECIAL ORDER

Eaton Bussmann series high speed British standard fuse, Single barrel, 25A, 690 VAC/500 VDC (IEC), 700 VAC/500 VDC (UL), Class aR, Breaking capacity 200 kA RMS Sym., 50 kA DC at 500 VDC

Fuse, Fuse-link, high speed, 25 A, AC 690 V, DC 500 V, BS88, 19 x 77 mm, aR, BS, offset bolted tags, DC common bus, DC drives, power converters/rectifiers and reduced voltage starters, BS88-4, IEC 60269-4, Breaking Capacity 200 kA, Optional accessories fuse-holder BH-0111

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Bussmann Series High speed fuses
--------------	--

Additional Product Information

General specifications

Product Name Eaton Bussmann series high speed british standard fuse Catalog Number 25FE EAN 5027590470148 UPC 051712422048 Product Length/Depth 82 mm Product Height 39 mm Product Width 91 mm Product Weight 37.9 g

Compliances CE Marked

RoHS Compliant Certifications BS88

IEC 60269

EAC

Designed and tested to BS88 part 4

IEC 60269-4 Electrical data

Amperage Rating 25 A Voltage rating 690 V (IEC), 700 V (UL) Rated voltage AC 690 V Rated voltage DC 500 V Interrupt rating 200 kA RMS Sym, 50 kA at 500 Vdc Class aR Product specifications

Application Semiconductor, DC Common bus, DC drives, power converters/rectifiers Fuse indicator None Compatible Trip indicator/Microswitch

Suitable for EC-600 Trip indicator kit (indicator + clips)

TI700 Fuse indicator

MAI Microswitch/adaptor

MBI Microswitch/adaptor

ETIM for 25FE Circuit breakers and fuses (EC004556)

Feature Name

Feature Value

Fuse system according to IEC 60269 (EF017676)

Other

Fuse construction type according to IEC 60269 (EF015865)

Other

Type of current (EF000143)

AC/DC

Rated voltage AC (EF007682)

690 V

Rated voltage DC (EF012281)

500 V

Rated current (EF000227)

25 A

Utilization category according to IEC 60269 (EF002572)

aR (accompanied semiconductor protection)

Breaking capacity (EF005617)

200 kA

Colour code (EF000931)

None

Type of fuse status indicator (EF004473)

None

Mounting holes (EF021553)

M6

Centre-to-centre distance of connections (EF021151)

61.8 mm

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / NOT STAND - SPECIAL ORDER with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.