

INDUSTRIAL COMPONENT DATA

NSD20M25 EATON ELECTRIC Emergency switching off key-operated button, 1N/O+1N/C, surface mounting

Brand: EATON - MOELLER | Manufacturer Part Number: NSD20M25



Manufacturer	EATON - MOELLER
MPN / Reference	NSD20M25
Catalog number	10000
Category	HRC fuse
Minimum order	20 Pcs
Document ID	EO-0C8C129B98
Generated	2026-08-06

Product Overview

550V INDR'L>NS20M25 (20) CARTON QTY. 20

Fuse-link, low voltage, 20A, AC 415 V, BS88/F2, 18 x 59 mm, gM, BS, 20M25

Fuse, Fuse-link, low voltage, AC 415 V, BS88/F2, 18 x 59 mm, gM, BS, offset bladed tags, motor-rated, general industrial applications, BS88-2, IEC 60269-2, Breaking Capacity 80 kA, Ceramic body, Optional accessories fuse-holder 32NNS and SC32

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Bussmann Series Low Voltage fuses and accessories
--------------	---

Additional Product Information

General specifications

Product Name Eaton Bussmann series low voltage british standard fuse Catalog Number NSD20M25 EAN 5027590504836

UPC 051712840293 Product Length/Depth 58.5 mm Product Height 13.8 mm Product Width 13.8 mm Product Weight 16.2

g Compliances CE Marked

RoHS Compliant Certifications IEC 60269-2

BS88 Electrical data

Amperage Rating 20 A Voltage rating 415 V Voltage type AC Breaking capacity 80 kA Class Class gM Compatible fuse holder

Suitable for 32NNS Safeloc fuse holder

SC32 Safeclip fuse holder Product specifications

Fuse type NSD Fitted with: Offset bladed tags Construction BS88/F2

ETIM for NSD20M25 Circuit breakers and fuses (EC004556)

Feature Name

Feature Value

Fuse system according to IEC 60269 (EF017676)

Fuse system E

Fuse construction type according to IEC 60269 (EF015865)

F2

Type of current (EF000143)

AC

Rated voltage AC (EF007682)

415 V

Rated current (EF000227)

20 A

Utilization category according to IEC 60269 (EF002572)

gM (motor protection)

Breaking capacity (EF005617)

80 kA

Colour code (EF000931)

None

Type of fuse status indicator (EF004473)

None

Power loss at rated current (EF012389)

1.2 W

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / NSD20M25 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.