

## INDUSTRIAL COMPONENT DATA

# NSD20M32 EATON ELECTRIC Emergency switching off key-operated button, 1N/O+1N/C, surface mounting

Brand: EATON - MOELLER | Manufacturer Part Number: NSD20M32



|                 |                 |
|-----------------|-----------------|
| Manufacturer    | EATON - MOELLER |
| MPN / Reference | NSD20M32        |
| Catalog number  | 10000           |
| Category        | HRC fuse        |
| Minimum order   | 20 Pcs          |
| Document ID     | EO-A48A4C53D0   |
| Generated       | 2026-08-06      |

## Product Overview

550V INDR'L>NS20M32 (20) CARTON QTY. 20

Fuse-link, LV, 20 A, AC 415 V, BS88/F1, 14 x 59 mm, gM, BS, 20M32

Fuse, Fuse-link, low voltage, 20 A, AC 550 V, BS88/F1, 14 x 59 mm, gM, BS, offset bladed tags, general industrial applications, BS88-2, IEC 60269-2, Breaking Capacity 80 kA, Optional accessories fuse-holder 32NNS SC32

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path EATON - MOELLER > Bussmann Series Low Voltage fuses and accessories

## Additional Product Information

### General specifications

Product Name Eaton Bussmann series low voltage british standard fuse Catalog Number NSD20M32 EAN 5027590504843

UPC 051712840309 Product Length/Depth 58.5 mm Product Height 13.8 mm Product Width 13.8 mm Product Weight

16.25 g Compliances CE Marked

RoHS Compliant Certifications IEC 60269-2

### BS88 Electrical data

Amperage Rating 20 A Voltage rating 415 V Voltage type AC Breaking capacity 80 kA Class Class gM Compatible fuse holder

Suitable for 32NNS Safeloc fuse holder

SC32 Safeclip fuse holder Product specifications

Fuse type NSD Fitted with: Offset bladed tags Construction BS88/F1

ETIM for NSD20M32 Circuit breakers and fuses (EC004556)

Feature Name  
Feature Value  
Fuse system according to IEC 60269 (EF017676)  
Fuse system E  
Fuse construction type according to IEC 60269 (EF015865)  
F1  
Type of current (EF000143)  
AC  
Rated voltage AC (EF007682)  
415 V  
Rated current (EF000227)  
20 A  
Utilization category according to IEC 60269 (EF002572)  
gM (motor protection)  
Breaking capacity (EF005617)  
80 kA  
Colour code (EF000931)  
None  
Type of fuse status indicator (EF004473)  
None  
Power loss at rated current (EF012389)  
0.95 W

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / NSD20M32 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.