

INDUSTRIAL COMPONENT DATA

NSD32M40 EATON ELECTRIC Fuse-link, LV, 32 A, AC 415 V, BS88/F2, 18 x 59 mm, gM, BS, 32M40

Brand: EATON - MOELLER | Manufacturer Part Number: NSD32M40



Manufacturer	EATON - MOELLER
MPN / Reference	NSD32M40
Catalog number	10000
Category	HRC fuse
Minimum order	20 Pcs
Document ID	EO-8BEE5A0D4E
Generated	2026-08-06

Product Overview

40A 415V M/S FUSE>(20) CARTON QTY. 20

Fuse-link, LV, 32 A, AC 415 V, BS88/F2, 18 x 59 mm, gM, BS, 32M40

Fuse, Fuse-link, low voltage, 32 A, AC 415 V, BS88/F2, 18 x 59 mm, gM, BS, offset bladed tags, general industrial applications, BS88-2, IEC 60269-2, Breaking Capacity 80 kA, Optional accessories fuse-holder 32NNS SC32

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Bussmann Series Low Voltage fuses and accessories

Additional Product Information

General specifications

Product Name Eaton Bussmann series low voltage british standard fuse Catalog Number NSD32M40 EAN 5027590504904

UPC 051712844505 Product Length/Depth 59 mm Product Height 18 mm Product Width 18 mm Product Weight 26 g

Compliances CE Marked

RoHS Compliant Certifications IEC 60269-2

BS88 Electrical data

Amperage Rating 40 A Voltage rating 415 V Voltage type AC Breaking capacity 80 kA Class Class gM Compatible fuse holder

Suitable for 32NNS Safeloc fuse holder

SC32 Safeclip fuse holder Product specifications

Fuse type NSD Fitted with: Offset bladed tags Construction BS88/F2

ETIM for NSD32M40 Circuit breakers and fuses (EC004556)

Feature Name
Feature Value
Fuse system according to IEC 60269 (EF017676)
Fuse system E
Fuse construction type according to IEC 60269 (EF015865)
F2
Type of current (EF000143)
AC
Rated voltage AC (EF007682)
415 V
Rated current (EF000227)
40 A
Utilization category according to IEC 60269 (EF002572)
gM (motor protection)
Breaking capacity (EF005617)
80 kA
Colour code (EF000931)
None
Type of fuse status indicator (EF004473)
None
Power loss at rated current (EF012389)
1.9 W

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / NSD32M40 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.