

INDUSTRIAL COMPONENT DATA

NSD32M50 EATON ELECTRIC Fuse-link, low voltage, 32A, AC 415 V, BS88/F2, 18 x 59 mm, gM, BS, 32M50

Brand: EATON - MOELLER | Manufacturer Part Number: NSD32M50



Manufacturer	EATON - MOELLER
MPN / Reference	NSD32M50
Catalog number	10000
Category	HRC fuse
Minimum order	20 Pcs
Document ID	EO-2E67AB6C4A
Generated	2026-08-06

Product Overview

50A 415V M/S FUSE>(20) CARTON QTY. 20

Fuse-link, low voltage, AC 415 V, BS88/F2, 18 x 59 mm, gM, BS

Fuse, Fuse-link, low voltage, AC 415 V, BS88/F2, 18 x 59 mm, gM, BS, offset bladed tags, motor-rated, general industrial applications, BS88-2, IEC 60269-2, Breaking Capacity 80 kA, Ceramic body, Optional accessories fuse-holder 32NNS and SC32

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Bussmann Series Low Voltage fuses and accessories

Additional Product Information

General specifications

Product Name Eaton Bussmann series low voltage british standard fuse Catalog Number NSD32M50 EAN 5027590504911

UPC 051712840330 Product Length/Depth 59 mm Product Height 18 mm Product Width 18 mm Product Weight 26.8 g

Compliances RoHS Compliant Electrical data

Amperage Rating 50 A Voltage rating 415 V Voltage type AC Breaking capacity 80 kA Class Class gM Compatible fuse holder

Suitable for 32NNS Safeloc fuse holder

SC32 Safeclip fuse holder Product specifications

Fuse type NSD Fitted with: Offset bladed tags Construction BS88/F2

ETIM for NSD32M50 Circuit breakers and fuses (EC004556)

Feature Name

Feature Value

Fuse system according to IEC 60269 (EF017676)

Fuse system E

Fuse construction type according to IEC 60269 (EF015865)

F2

Type of current (EF000143)

AC

Rated voltage AC (EF007682)

415 V

Rated current (EF000227)

50 A

Utilization category according to IEC 60269 (EF002572)

gM (motor protection)

Breaking capacity (EF005617)

80 kA

Colour code (EF000931)

None

Type of fuse status indicator (EF004473)

None

Power loss at rated current (EF012389)

1.4 W

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / NSD32M50 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.