

INDUSTRIAL COMPONENT DATA

NWS-TKT 255420 EATON ELECTRIC Door contact with plug-in connection

Brand: EATON - MOELLER | Manufacturer Part Number: NWS-TKT



Manufacturer	EATON - MOELLER
MPN / Reference	NWS-TKT
Catalog number	255420
Category	End switch
Minimum order	1 Pcs
Document ID	EO-541DE49C7A
Generated	2026-08-05

Product Overview

Door contact with plug-in connection

Micro Detection Cabinet Door

Door contact with plug-in connection, 1 N/C and 1 N/O, IP65 degree of protection, material characteristic insulated material, circuit-breaker data: 230 V AC / 6 A the door contact is used to switch cabinet lights on and off., Equipment supplied: 1 door contact, 1 connecting cable, various fixing material

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Enclosures
--------------	------------------------------

Additional Product Information

General specifications

Product Name Eaton Distribution parts Catalog Number 255420 Model Code NWS-TKT EAN 4015082554200 Product Length/Depth 300 mm Product Height 110 mm Product Width 180 mm Product Weight 0.055 kg Compliances CE Marked RoHS conform Product specifications

Electric connection type Cable entry metrical Enclosure material finishing Other Actuator alignment Other Enclosure material Plastic Enclosure type Other Special features Type General switchboard accessory for panel building Explosion safety category for dust None Switch type Quick-break switch Explosion safety category for gas None Degree of Protection IP65 Interface type None Accessories Control panel lighting Actuator type Plunger Unit type Accessories Ambient operating temperature - max 70 °C Ambient operating temperature - min -25 °C Functions Accessory Number of contacts (change-over contacts) 0 Number of contacts (normally closed contacts) 1 Number of contacts (normally open contacts) 1 Number of safety auxiliary contacts 2 Rated operational current (Ie) at AC-15, 125 V 6 A Rated operational current (Ie) at

AC-15, 220 V, 230 V, 240 V 6 A Rated operational current (Ie) at AC-15, 24 V 6 A Rated operational current (Ie) at DC-13, 125 V 0.3 A Rated operational current (Ie) at DC-13, 220 V, 230 V 0.8 A Rated operational current (Ie) at DC-13, 24 V 3 A
Sensor diameter 8.2 mm Sensor height 74 mm Sensor length 76 mm Sensor width 30 mm

ETIM for 255420 Sensors (EC000030)

Feature Name

Feature Value

Width sensor...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / NWS-TKT with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.