

INDUSTRIAL COMPONENT DATA

NZM-XMC-MDISP70 172766 EATON ELECTRIC

NZM-XMC-MDISP70 BreakerVisu visualization and logging system, 24 VDC, ..

Brand: EATON - MOELLER | Manufacturer Part Number: NZM-XMC-MDISP70



Manufacturer	EATON - MOELLER
MPN / Reference	NZM-XMC-MDISP70
Catalog number	172766
Category	Graphic panel
Minimum order	1 Pcs
Document ID	EO-5A941E4D77
Generated	2026-08-04

Product Overview

NZM-XMC-MDISP70 BreakerVisu - visualization and logging system, 24 VDC, 7 inch, TFT color display, SmartWire-DT, Modbus RTU, Ethernet

Touch display, XV-102, Product range: XV100 5.7z, Subrange: Touch display with integrated controller BreakerVisu (HMI-PLC), Function: Visualize and log circuit-breaker and/or measuring device data, Max. 32 devices via MODBUS RTU and/or max. 16 devices via SmartWire-DT, Common features of the model series: Read diagnostic memories, Create energy logs, Connect NZM using NZM-XSWD-704, Connect all NZM...-XMC-MB... measuring modules and NZM-XMC-TC-MB, Connection of IZMX16/40 using IZMX-MCAM, Connect IZM26... using IZM-MMINT, Connect PKE with XTUA or XTUWA using PKE-SWD-SP, Connect PKE with XTUACP or XTUWACP using PKE-SWD-CP, Connect RCCBs, MCBs , RCBOs using MCB-HK-SWD, Ethernet connection for display on web browsers, FTP connection for data transfers, Gateway function for forwarding data, Non-Eaton devices can be connected, Display - Type: Color display, TFT, Touch-technology: Resistive-Touch, Number of colors: 64 k Colors, Resolution: WVGA, 800 x 480 Pixel, Portrait format: no, Screen diagonal: 7 Inch, Insulating enclosure and front plate, Operating system: Windows CE 5.0 (license incl.), PLC-license: PLC license inclusive, License certificates for onboard interfaces: Can be expanded as required, see Accessories -> License product certificates , built-in...

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > Circuit Breakers NZM Accessories**

Additional Product Information

BreakerVisu - visualization and logging system, 24 VDC, 7 inch, TFT color display, SmartWire-DT, Modbus RTU, Ethernet Alternate Catalog No. NZM-XMC-MDISP70 EL-Nummer (Norway) 0004315599 Touch display, XV-102, Product range: XV100 5.7", Subrange: Touch display with integrated controller BreakerVisu (HMI-PLC), Function: Visualize and log circuit-breaker and/or measuring device data, Max. 32 devices via MODBUS RTU and/or max. 16 devices via SmartWire-DT, Common features of the model series: Read diagnostic memories, Create energy logs, Connect NZM using NZM-XSWD-704, Connect all NZM...-XMC-MB... measuring modules and NZM-XMC-TC-MB, Connection of IZMX16/40 using IZMX-MCAM, Connect IZM26... using IZM-MMINT, Connect PKE with XTUA or XTUWA using PKE-SWD-SP, Connect PKE with XTUACP or XTUWACP using PKE-SWD-CP, Connect RCCBs, MCBs, RCBOs using MCB-HK-SWD, Ethernet connection for display on web browsers, FTP connection for data transfers, Gateway function for forwarding data, Non-Eaton devices can be connected, Display - Type: Color display, TFT, Touch-technology: Resistive-Touch, Number of colours: 64 k Colours, Resolution: WVGA, 800 x 480 Pixel, Portrait format: no, Screen diagonal: 7 Inch, Insulating enclosure and front plate, Operating system: Windows CE 5.0 (licence incl.), PLC-licence: PLC licence inclusive, License certificates for onboard interfaces: Can be expanded as required, see Accessories -> License product certificates, built-in interfaces: 1 x Ethernet 100base-TX/10base-T, 1...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / NZM-XMC-MDISP70 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.