

INDUSTRIAL COMPONENT DATA

NZM2/3-X2A 189722 Y7-189722 EATON ELECTRIC Relay module for NZM2/3, configurable, 2NO, 24DC, 24-230AC, PI

Brand: EATON - MOELLER | Manufacturer Part Number: NZM2/3-X2A



Manufacturer	EATON - MOELLER
MPN / Reference	NZM2/3-X2A
Catalog number	Y7-189722
Category	Accessories/spare parts for low-voltage switch technology
Minimum order	1 Pcs
Document ID	EO-A1F9A10DF5
Generated	2026-08-03

Product Overview

Relay module for NZM2/3, configurable, 2NO, 24DC, 24-230AC, PI
NZM2/3-X2A

Eaton Moeller series NZM - Molded Case Circuit Breaker. Relay module for NZM2/3, configurable, 2NO, 24DC, 24-230AC, PI

Optional accessories for the circuit-breaker series NZM offers a comprehensive portfolio of application options for use world wide. The mounting is always flexible and easy thanks to the modular function groups. Notes: Relais modules with two relays. For signaling commands or different states of the circuit-breaker. Two relays per unit. Actuation reason can be configured in the trip unit. Configuration via communication or circuit breaker display or front USB connection and Eaton Power Xpert Protection Manager. Only suitable for use in conjunction with circuit-breakers with electronic releases . Relais modules cannot be installed simultaneously with early-make contact NZM...-XHIV, or undervoltage release NZM...-XU..., or shunt release NZM...-XA... Relay coil actuated by trip unit. Relay contact

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Circuit Breakers NZM
--------------	--

Additional Product Information

General specifications

Product Name Eaton Moeller series NZM release Catalog Number 189722 Model Code NZM2/3-X2A EAN 4015081877171
Product Length/Depth 115 mm Product Height 65 mm Product Width 75 mm Product Weight 0.06 kg Compliances UL/CSA IEC

RoHS conform Certifications UL listed

CSA (Class No. 1437-01)

CSA certified

UL (Category Control Number DIHS)

CE marking

UL (File No. E140305)

IEC60947

UL489

CSA-C22.2 No. 5-09

CSA (File No. 22086) Product specifications

Type Accessory Relay module Special features For signaling commands or different states of the circuit-breaker. Two relays per unit. The activation criteria can be configured in the trip unit. Configuration via communication or circuit breaker display or front USB port and Eaton Power Xpert Protection Manager. Only for use in combination with circuit-breakers with electronic trips. Relay components cannot be installed simultaneously with make-before-break auxiliary breaker NZM...-XHIV, the under-voltage trip NZM...-XU.... or the shunt trip NZM...-XA.... Relay contacts for control wiring. Relays can be used for controlling remote operator with $U_s=208-204\text{ V AC}$. Control wiring on push-in clamps. Cannot be used with the PXR10 NZM-AX electronic trip. 10.10 Temperature rise The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices. 10.11 Short-circuit rating Is the panel builder's responsibility. The specifications for the switchgear must be observed. 10.12 Elec...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / NZM2/3-X2A with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.