

INDUSTRIAL COMPONENT DATA

NZM2/3-XA110-130AC/DC-PI 189802 Y7-189802 EATON ELECTRIC NZM2/3-XA110-130AC/DC-PI

Brand: EATON - MOELLER | Manufacturer Part Number: NZM2/3-XA110-130AC/DC-PI



Manufacturer	EATON - MOELLER
MPN / Reference	NZM2/3-XA110-130AC/DC-PI
Catalog number	Y7-189802
Category	Shunt release (for power circuit breaker)
Minimum order	1 Pcs
Document ID	EO-E60C5BEB00
Generated	2026-08-05

Product Overview

NZM2/3-XA110-130AC/DC-PI

Shunt release for NZM2/3, 110-130AC/DC, Push-in terminals

Optional accessories for the circuit-breaker series NZM offers a comprehensive portfolio of application options for use world wide. The mounting is always flexible and easy thanks to the modular function groups. Notes: Shunt releases with push-in terminals. Switches are tripped by a voltage pulse or by the application of uninterrupted voltage. When the shunt release is live, contact with the circuit-breaker's main contacts on switching on is reliably prevented. Shunt release modules cannot be installed simultaneously with early-make contact NZM...-XHIV, undervoltage release NZM...-XU..., or relays modules NZM...-X2A...

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Circuit Breakers NZM

Additional Product Information

Shunt release for NZM2/3, 110-130AC/DC, Push-in terminalsOptional accessories for the circuit-breaker series NZM offers a comprehensive portfolio of application options for use world wide. The mounting is always flexible and easy thanks to the modular function groups. Notes: Shunt releases with push-in terminals. Switches are tripped by a voltage pulse or by the application of uninterrupted voltage. When the shunt release is live, contact with the circuit-breaker's main contacts on switching on is reliably prevented. Shunt release modules cannot be installed simultaneously with early-make contact NZM...-XHIV, undervoltage release NZM...-XU..., or relays modules NZM...-X2A...Delivery program

Product rangeAccessoriesAccessoriesShunt releaseAccessoriesShunt releasesStandard/ApprovalUL/CSA, IECConstruction sizeNZM2/3DescriptionWhen the shunt release is live, contact with the circuit-breaker's main contacts on

switching on is reliably prevented.

Shunt release modules cannot be installed simultaneously with early-make contact NZM...-XHIV, undervoltage release NZM...-XU..., or relays modules NZM...-X2A... Connection type with push in terminal Auxiliary contacts without auxiliary contact Rated control voltage [Us] 110 - 130 V AC/DC V For use with NZM2(-4), N(S)2(-4)

NZM3(-4), N(S)3(-4) Design verification as per IEC/EN 61439

IEC/EN 61439 design verification 10.2 Strength of materials and parts 10.2.2 Corrosion resistance Meets the product standard's requirements. 10.2 Strength of materials and parts 10.2.3.1...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / NZM2/3-XA110-130AC/DC-PI with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.