

INDUSTRIAL COMPONENT DATA

NZM2/3-XA2A110-130AC 189742 Y7-189742 EATON ELECTRIC NZM2/3-XA2A110-130AC

Brand: EATON - MOELLER | Manufacturer Part Number: NZM2/3-XA2A110-130AC



Manufacturer	EATON - MOELLER
MPN / Reference	NZM2/3-XA2A110-130AC
Catalog number	Y7-189742
Category	Shunt release (for power circuit breaker)
Minimum order	1 Pcs
Document ID	EO-9AC6965E56
Generated	2026-08-05

Product Overview

NZM2/3-XA2A110-130AC

Shunt release for NZM2/3, configurable relays, 2NO, 110-130AC, Push-in terminals

Optional accessories for the circuit-breaker series NZM offers a comprehensive portfolio of application options for use world wide. The mounting is always flexible and easy thanks to the modular function groups. Notes: Shunt releases with two relays. Switches are tripped by a voltage pulse or by the application of uninterrupted voltage. For signaling commands or different states of the circuit-breaker. Two relays per unit. Actuation reason can be configured in the trip unit. Configuration via communication or circuit breaker display or front USB connection and Eaton Power Xpert Protection Manager . When the shunt release is live, contact with the circuit-breaker's main contacts on switching on is reliably prevented. Only suitable for use in conjunction with circuit-breakers with electronic releases. Shunt release relais modules cannot be installed simultaneously with early-make contact NZM...-XHIV, or undervoltage release NZM...-XU..., or shunt release NZM...-XA... Relay coil actuated by trip unit. Relay contact for control wiring. Control wiring to push-in terminals. Cannot be used with PXR10 NZM-AE electronic release.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Circuit Breakers NZM

Additional Product Information

Shunt release for NZM2/3, configurable relays, 2NO, 110-130AC, Push-in terminalsOptional accessories for the circuit-breaker series NZM offers a comprehensive portfolio of application options for use world wide. The mounting is always flexible and easy thanks to the modular function groups. Notes: Shunt releases with two relays. Switches are tripped by a voltage pulse or by the application of uninterrupted voltage. For signaling commands or different states of the

circuit-breaker. Two relays per unit. Actuation reason can be configured in the trip unit. Configuration via communication or circuit breaker display or front USB connection and Eaton Power Xpert Protection Manager. When the shunt release is live, contact with the circuit-breaker's main contacts on switching on is reliably prevented. Only suitable for use in conjunction with circuit-breakers with electronic releases. Shunt release relays modules cannot be installed simultaneously with early-make contact NZM...-XHIV, or undervoltage release NZM...-XU..., or shunt release NZM...-XA... Relay coil actuated by trip unit. Relay contact for control wiring. Control wiring to push-in terminals. Cannot be used with PXR10 NZM-AE electronic release. Delivery program

Product range Accessories Accessories Shunt release Accessories Shunt release with two relays Standard/Approval UL/CSA, IEC Construction size NZM2/3 Description The breakers are actuated by a voltage pulse or by applying a no-break current. For signaling commands or different states...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / NZM2/3-XA2A110-130AC with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.