

INDUSTRIAL COMPONENT DATA

NZM2/3-XA2A208-240AC 189743 Y7-189743 EATON ELECTRIC NZM2/3-XA2A208-240AC

Brand: EATON - MOELLER | Manufacturer Part Number: NZM2/3-XA2A208-240AC



Manufacturer	EATON - MOELLER
MPN / Reference	NZM2/3-XA2A208-240AC
Catalog number	Y7-189743
Category	Shunt release (for power circuit breaker)
Minimum order	1 Pcs
Document ID	EO-4DEC60A5DA
Generated	2026-08-06

Product Overview

NZM2/3-XA2A208-240AC

Eaton Moeller series NZM - Molded Case Circuit Breaker. Shunt release for NZM2/3, configurable relays, 2NO, 208-240AC, Push-in terminals

Optional accessories for the circuit-breaker series NZM offers a comprehensive portfolio of application options for use world wide. The mounting is always flexible and easy thanks to the modular function groups. Notes: Shunt releases with two relays. Switches are tripped by a voltage pulse or by the application of uninterrupted voltage. For signaling commands or different states of the circuit-breaker. Two relays per unit. Actuation reason can be configured in the trip unit. Configuration via communication or circuit breaker display or front USB connection and Eaton Power Xpert Protection Manager . When the shunt release is live, contact with the circuit-breaker's main contacts on switching on is reliably prevented. Only suitable for use in conjunction with circuit-breakers with electronic releases. Shunt release relais modules cannot be installed simultaneously with early-make contact NZM...-XHIV, or undervoltage release NZM...-XU..., or shunt release NZM...-XA... Relay coil actuated by trip unit. Relay contact for control wiring. Control wiring to push-in terminals. Cannot be used with PXR10 NZM-AE electronic release.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Circuit Breakers NZM
--------------	--

Additional Product Information

General specifications

Product Name Eaton Moeller series NZM release Catalog Number 189743 Model Code NZM2/3-XA2A208-240AC EAN 4015081877386 Product Length/Depth 115 mm Product Height 65 mm Product Width 75 mm Product Weight 0.08 kg

Compliances UL/CSA

IEC

RoHS conform Certifications CSA certified

CE marking

CSA-C22.2 No. 5-09

CSA (Class No. 1437-01)

CSA (File No. 22086)

UL (Category Control Number DIHS)

UL (File No. E140305)

IEC60947

UL489

UL listed Product specifications

Type Special features The breakers are actuated by a voltage pulse or by applying a no-break current.

For signaling commands or different states of the circuit-breaker.

Two relays per unit.

The activation criteria can be configured in the trip unit.

Configuration via communication or circuit breaker display or front USB port and Eaton Power Xpert Protection Manager.

If the shunt trip is live, contact with the circuit breaker's primary contacts is prevented when switched on.

Only for use in combination with circuit-breakers with electronic trips.

Shunt trip relay modules cannot be installed simultaneously with make-before-break auxiliary contact NZM...-XHIV, under-voltage trip NZM...-XU... or shunt trip NZM...-XA.

Relay coil is controlled by trip unit.

Relay contacts for control wiring.

Relays can be used for controlling remote operator with $U_s=208-204$ V AC.

Control wiring on push-in clamps.

Cannot be used with the PXR10 NZM-AX electronic trip.

Voltage rating $0.7 - 1.1 \times U_s$ 10.10 Temperature rise The panel...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / NZM2/3-XA2A208-240AC with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.