

INDUSTRIAL COMPONENT DATA

NZM2/3-XU2A110-130AC 189726 Y7-189726 EATON ELECTRIC NZM2/3-XU2A110-130AC

Brand: EATON - MOELLER | Manufacturer Part Number: NZM2/3-XU2A110-130AC



Manufacturer	EATON - MOELLER
MPN / Reference	NZM2/3-XU2A110-130AC
Catalog number	Y7-189726
Category	Under voltage coil
Minimum order	1 Pcs
Document ID	EO-0F8FBAECBC
Generated	2026-08-04

Product Overview

NZM2/3-XU2A110-130AC

Undervoltage release for NZM2/3, configurable relays, 2NO, 110-130AC, Push-in terminals

Optional accessories for the circuit-breaker series NZM offers a comprehensive portfolio of application options for use world wide. The mounting is always flexible and easy thanks to the modular function groups. Notes: Undervoltage releases with two relays. Non-delayed disconnection of circuit-breaker NZM when control voltage drops below 35 - 70 % Us. For use with emergency switching off devices in conjunction with emergency switching off button. For signaling commands or different states of the circuit-breaker. Two relays per unit. Actuation reason can be configured in the trip unit . Configuration via communication or circuit breaker display or front USB connection and Eaton Power Xpert Protection Manager. When the undervoltage release is de-energized, accidental contact with the main contacts of the circuit-breaker during attempts to switch on is reliably prevented. Only suitable for use in conjunction with circuit-breakers with electronic releases.

Undervoltage release relays modules cannot be installed simultaneously with early-make contact NZM...-XHIV, or undervoltage release NZM...-XU..., or shunt release NZM...-XA... Relay coil actuated by trip unit. Relay contact for control wiring. Control wiring to push-in terminals . Cannot be used with PXR10 NZM-AE electronic rele...

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Circuit Breakers NZM

Additional Product Information

Undervoltage release for NZM2/3, configurable relays, 2NO, 110-130AC, Push-in terminalsOptional accessories for the circuit-breaker series NZM offers a comprehensive portfolio of application options for use world wide. The mounting is always flexible and easy thanks to the modular function groups. Notes: Undervoltage releases with two relays. Non-delayed

disconnection of circuit-breaker NZM when control voltage drops below 35 - 70 % Us. For use with emergency switching off devices in conjunction with emergency switching off button. For signaling commands or different states of the circuit-breaker. Two relays per unit. Actuation reason can be configured in the trip unit. Configuration via communication or circuit breaker display or front USB connection and Eaton Power Xpert Protection Manager. When the undervoltage release is de-energized, accidental contact with the main contacts of the circuit-breaker during attempts to switch on is reliably prevented. Only suitable for use in conjunction with circuit-breakers with electronic releases. Undervoltage release relays modules cannot be installed simultaneously with early-make contact NZM...-XHIV, or undervoltage release NZM...-XU..., or shunt release NZM...-XA... Relay coil actuated by trip unit. Relay contact for control wiring. Control wiring to push-in terminals. Cannot be used with PXR10 NZM-AE electronic release. Delivery program

Product range Accessories Accessories Undervoltage release Accessories Undervoltage release with two relays S...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / NZM2/3-XU2A110-130AC with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.