

INDUSTRIAL COMPONENT DATA

NZM2/3-XUHIV60DC-PI 189783 Y7-189783 EATON ELECTRIC

NZM2/3-XUHIV60DC-PI

Brand: EATON - MOELLER | Manufacturer Part Number: NZM2/3-XUHIV60DC-PI



Manufacturer	EATON - MOELLER
MPN / Reference	NZM2/3-XUHIV60DC-PI
Catalog number	Y7-189783
Category	Under voltage coil
Minimum order	1 Pcs
Document ID	EO-32170E13A3
Generated	2026-08-04

Product Overview

NZM2/3-XUHIV60DC-PI

Eaton Moeller series NZM - Molded Case Circuit Breaker. Undervoltage release for NZM2/3, 1 early-make auxiliary contact, 2NO, 60DC, Push-in terminals

Optional accessories for the circuit-breaker series NZM offers a comprehensive portfolio of application options for use world wide. The mounting is always flexible and easy thanks to the modular function groups. Notes: Undervoltage releases with one early-make contact and push-in terminals. For interlocking and load-shedding circuits, as well as for early-make of the undervoltage release in main-switch applications. Non-delayed disconnection of circuit-breaker NZM when control voltage drops below 35 - 70 % Us. For use with emergency switching off devices in conjunction with emergency switching off button . When the undervoltage release is de-energized, accidental contact with the main contacts of the circuit-breaker during attempts to switch on is reliably prevented. Early-make of auxiliary contacts on switching on and off (manual operation): approx. 20 ms (NZM2/3) and 90 ms (NZM4). Undervoltage release modules cannot be installed simultaneously with early-make contact NZM...-XHIV, shunt release NZM...-XA... or relays modules NZM...-X2A...

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Circuit Breakers NZM
--------------	--

Additional Product Information

General specifications

Product Name Eaton Moeller series NZM release Catalog Number 189783 Model Code NZM2/3-XUHIV60DC-PI EAN 4015081877782 Product Length/Depth 115 mm Product Height 65 mm Product Width 75 mm Product Weight 0.08 kg
Compliances IEC

UL/CSA

RoHS conform Product specifications

Used with NZM3(-4), N(S)3(-4)

NZM2(-4), N(S)2(-4) Type Accessory Undervoltage release Undervoltage release with early-make auxiliary contact Special features For interlocking and load-shedding circuits, as well as for early-make of the undervoltage release in main-switch applications. Instantaneous shut-off of the NZM circuit breaker when the control voltage drops below 35 - 70% Us. For use with emergency-stop devices in connection with an emergency-stop button. When the under-voltage trip is switched off, accidental contact with the circuit breaker's primary contacts is prevented when switched on. Early-make of auxiliary contacts on switching on and off (manual operation): approx. 20 ms (NZM2/3) and 90 ms (NZM4). Undervoltage release modules cannot be installed simultaneously with early-make contact NZM...-XHIV, shunt release NZM...-XA... or relais modules NZM...-X2A... 10.10 Temperature rise The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices. 10.11 Short-circuit rating Is the panel builder's responsibility. The specifications for the switchgear must be observed. 10.12 Electromagnetic compatibility Is the panel builder's resp...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / NZM2/3-XUHIV60DC-PI with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.