

INDUSTRIAL COMPONENT DATA

NZM3-4-XSVS 168473 Y7-168473 EATON ELECTRIC 168473 NZM3-4-XSVS

Brand: EATON - MOELLER | Manufacturer Part Number: NZM3-4-XSVS



Manufacturer	EATON - MOELLER
MPN / Reference	NZM3-4-XSVS
Catalog number	Y7-168473
Category	Chassis part power circuit breaker
Minimum order	1 Pcs
Document ID	EO-A612B6072E
Generated	2026-08-02

Product Overview

168473 NZM3-4-XSVS

NZM3-4-XSVS

Socket, 4p, 630A

Optional accessories for circuit-breaker series NZM offers a comprehensive portfolio of application possibilities for worldwide use. Modular functional groups make mounting flexible and simple.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Circuit Breakers NZM

Additional Product Information

Socket, 4p, 630AOptional accessories for circuit-breaker series NZM offers a comprehensive portfolio of application possibilities for worldwide use. Modular functional groups make mounting flexible and simple.

General specificationsProduct nameEaton Moeller series NZM plug-in unitPart

no.NZM3-4-XSVSEAN4015081649549Product Length/Depth345 millimetreProduct height132 millimetreProduct width185 millimetreProduct weight3.66 kilogramCompliancesIEC

RoHS conformCertificationsIEC/EN 60947Product TradenameNZMProduct TypeAccessoriesProduct Sub TypePlug-in unitDelivery programTypeAccessoryPlug-in socket for basic unitNumber of polesFour-poleNominal current500

AFeaturesVersion as built-in deviceFrameNZM3Technical Data - ElectricalElectrical connection type of main circuitScrew connectionIsolation500 V AC (between auxiliary contacts and main contacts)

300 V AC (between the auxiliary contacts)Direction of incoming supplyAs requiredTechnical Data - MechanicalMounting MethodPlug-in unitMounting positionVertical and 90° right/leftDegree of protectionIP2X (in the area of the plug-in

area)Protection against direct contactFinger and back-of-hand proof to VDE 0106 part 100Shock resistance20 g
(half-sinusoidal shock 20 ms)Climatic proofingDamp heat, cyclic, to IEC 60068-2-30
Damp heat, constant, to IEC 60068-2-78Technical Data - Mechanical - TerminalsTerminal equipment includedScrew
connectionDesign verification as per IEC/EN 61439 - technical dataEquipment heat dissipation, current-dependent83.3...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / NZM3-4-XSVS with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.