

INDUSTRIAL COMPONENT DATA

NZM4-XU2A110-130AC 189730 EATON ELECTRIC minimum voltage trigger for NZM4, configurable relays, 2NO, 110-130..

Brand: EATON - MOELLER | Manufacturer Part Number: NZM4-XU2A110-130AC



Manufacturer	EATON - MOELLER
MPN / Reference	NZM4-XU2A110-130AC
Catalog number	Y7-189730
Category	Under voltage coil
Minimum order	1 Pcs
Document ID	EO-D4D8A915BF
Generated	2026-08-05

Product Overview

minimum voltage trigger for NZM4, configurable relays, 2NO, 110-130AC, spring push-in terminals

Optional accessories for the circuit-breaker series NZM offers a comprehensive portfolio of application options for use world wide. The mounting is always flexible and easy thanks to the modular function groups. Notes: Undervoltage releases with two relays. Non-delayed disconnection of circuit-breaker NZM when control voltage drops below 35 - 70 % Us. For use with emergency switching off devices in conjunction with emergency switching off button. For signaling commands or different states of the circuit-breaker. Two relays per unit. Actuation reason can be configured in the trip unit . Configuration via communication or circuit breaker display or front USB connection and Eaton Power Xpert Protection Manager. When the undervoltage release is de-energized, accidental contact with the main contacts of the circuit-breaker during attempts to switch on is reliably prevented. Only suitable for use in conjunction with circuit-breakers with electronic releases. Undervoltage release relays modules cannot be installed simultaneously with early-make contact NZM...-XHIV, or undervoltage release NZM...-XU..., or shunt release NZM...-XA... Relay coil actuated by trip unit. Relay contact for control wiring. Control wiring to push-in terminals . Cannot be used with PXR10 NZM-AE electronic release.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Circuit Breakers NZM
--------------	--

Additional Product Information

General specifications

Product Name Eaton Moeller series NZM release Catalog Number 189730 Model Code NZM4-XU2A110-130AC EAN 4015081877256 Product Length/Depth 115 mm Product Height 65 mm Product Width 75 mm Product Weight 0.245 kg
Compliances IEC

UL/CSA

RoHS conform Certifications UL489

CSA certified

CSA (Class No. 1437-01)

UL (Category Control Number DIHS)

UL listed

CSA-C22.2 No. 5-09

IEC60947

CSA (File No. 22086)

UL (File No. E140305)

CE marking Product specifications

Used with PXR20(25) NZM4(-4)-...X... Type Accessory Undervoltage release Undervoltage release with two relays Special features Instantaneous shut-off of the NZM circuit breaker when control voltage drops below 35 - 70% Us For use with emergency-stop devices and an emergency-stop button For signaling commands or different states of the circuit-breaker Two relays per unit Actuation reason can be configured in the trip unit Configuration via communication or circuit breaker display or front USB connection and Eaton Power Xpert Protection Manager When the under-voltage trip is switched off, accidental contact with the circuit breaker's primary contacts is prevented when switched on Only for use in combination with circuit-breakers with electronic trips Undervoltage release modules cannot be installed with early-make contact NZM...-XHIV, shunt release NZM...-XA... or relais modules NZM...-X2A.. Relay coil is controlled by trip unit Push-in relay contact for control wiring Relays can be used for controlling remote operator with Us=20...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / NZM4-XU2A110-130AC with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.