

INDUSTRIAL COMPONENT DATA

NZM4-XU2A24AC 189728 Y7-189728 EATON ELECTRIC NZM4-XU2A24AC

Brand: EATON - MOELLER | Manufacturer Part Number: NZM4-XU2A24AC



Manufacturer	EATON - MOELLER
MPN / Reference	NZM4-XU2A24AC
Catalog number	Y7-189728
Category	Under voltage coil
Minimum order	1 Pcs
Document ID	EO-46D8975097
Generated	2026-08-03

Product Overview

NZM4-XU2A24AC

NZM4-XU2A24AC. Undervoltage release for NZM4, configurable relays, 2NO, 24AC, Push-in terminals

Optional accessories for the circuit-breaker series NZM offers a comprehensive portfolio of application options for use world wide. The mounting is always flexible and easy thanks to the modular function groups. Notes: Undervoltage releases with two relays. Non-delayed disconnection of circuit-breaker NZM when control voltage drops below 35 - 70 % Us. For use with emergency switching off devices in conjunction with emergency switching off button. For signaling commands or different states of the circuit-breaker. Two relays per unit. Actuation reason can be configured in the trip unit . Configuration via communication or circuit breaker display or front USB connection and Eaton Power Xpert Protection Manager. When the undervoltage release is de-energized, accidental contact with the main contacts of the circuit-breaker during attempts to switch on is reliably prevented. Only suitable for use in conjunction with circuit-breakers with electronic releases.

Undervoltage release relays modules cannot be installed simultaneously with early-make contact NZM...-XHIV, or undervoltage release NZM...-XU..., or shunt release NZM...-XA... Relay coil actuated by trip unit. Relay contact for control wiring. Control wiring to push-in terminals . Cannot be used with PXR10 NZM-AE electronic rel...

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Circuit Breakers NZM

Additional Product Information

General specifications

Product Name Eaton Moeller series NZM release Catalog Number 189728 Model Code NZM4-XU2A24AC EAN 4015081877232 Product Length/Depth 110 mm Product Height 63 mm Product Width 62 mm Product Weight 0.245 kg

Compliances IEC

UL/CSA

RoHS conform Certifications UL489

CSA (File No. 22086)

UL (Category Control Number DIHS)

CE marking

UL listed

CSA certified

UL (File No. E140305)

CSA (Class No. 1437-01)

IEC60947

CSA-C22.2 No. 5-09 Product specifications

Used with PXR20(25) NZM4(-4)-...X... Type Accessory Undervoltage release Undervoltage release with two relays Special features Instantaneous shut-off of the NZM circuit breaker when the control voltage drops below 35 - 70% Us For use with emergency-stop devices in connection with an emergency-stop button For signaling commands or different states of the circuit-breaker Two relays per unit The activation criteria can be configured in the trip unit Configuration via communication, circuit breaker display, front USB port and Eaton Power Xpert Protection Manager When the under-voltage trip is switched off, accidental contact with the circuit breaker's primary contacts is prevented when switched on Only for use with circuit-breakers with electronic trips Under-voltage trip relay modules cannot be installed simultaneously with make-before-break auxiliary contact NZM...-XHIV, under-voltage trip NZM...-XU... or shunt trip NZM...-XA Push-in clamp relay contacts for control wiring Relays can be used for controlling remote operator with...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / NZM4-XU2A24AC with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten PI #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.