

INDUSTRIAL COMPONENT DATA

NZM4-XUHIV2A24AC 189736 EATON ELECTRIC minimum voltage trigger for NZM4, configurable relays, 2NO, 1 aux con..

Brand: EATON - MOELLER | Manufacturer Part Number: NZM4-XUHIV2A24AC



Manufacturer	EATON - MOELLER
MPN / Reference	NZM4-XUHIV2A24AC
Catalog number	189736
Category	Under voltage coil
Minimum order	1 Pcs
Document ID	EO-F61A671A33
Generated	2026-08-04

Product Overview

minimum voltage trigger for NZM4, configurable relays, 2NO, 1 aux contact. advanced, 1NO, 24AC, Spring Push-in terminals

Optional accessories for the circuit-breaker series NZM offers a comprehensive portfolio of application options for use world wide. The mounting is always flexible and easy thanks to the modular function groups. Notes: Undervoltage releases with one early-make contact and two relays. For interlocking and load-shedding circuits, as well as for early-make of the undervoltage release in main-switch applications. Non-delayed disconnection of circuit-breaker NZM when control voltage drops below 35 - 70 % Us. For use with emergency switching off devices in conjunction with emergency switching off button . For signaling commands or different states of the circuit-breaker. Two relays per unit. Actuation reason can be configured in the trip unit. Configuration via communication or circuit breaker display or front USB connection and Eaton Power Xpert Protection Manager. When the undervoltage release is de-energized, accidental contact with the main contacts of the circuit-breaker during attempts to switch on is reliably prevented. Early-make of auxiliary contacts on switching on and off (manual operation): approx. 20 ms (NZM2/3) and 90 ms (NZM4). Only suitable for use in conjunction with circuit-breakers with electronic releases . Cannot be used in conjunction with...

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > Circuit Breakers NZM**

Additional Product Information

ETIM for 189736 Low-voltage industrial controls and switchgear (EC001022)

Feature Name

Feature Value

Rated control supply voltage AC 50 Hz (EF003978)
24 V
Rated control supply voltage AC 60 Hz (EF003979)
24 V
Rated control supply voltage DC (EF003980)
0 V
Voltage type for actuating (EF008242)
AC
Type of electric connection (EF003961)
Screw connection
Number of contacts as normally open contact (EF008256)
3
Number of contacts as normally closed contact (EF008255)
0
Number of contacts as change-over contact (EF008257)
0
Delayed (EF001541)
No
Suitable for power circuit breaker (EF005863)
No
Suitable for off-load switch (EF001543)
Yes
Suitable for motor safety switch (EF005826)
Yes
Suitable for overload relay (EF001545)
No

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / NZM4-XUHIV2A24AC with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.