

INDUSTRIAL COMPONENT DATA

NZM4-XUHIV48DC-PI 189794 EATON ELECTRIC minimum voltage trigger for NZM4, 1 contact aux. forward, 2NO, 48DC,..

Brand: EATON - MOELLER | Manufacturer Part Number: NZM4-XUHIV48DC-PI



Manufacturer	EATON - MOELLER
MPN / Reference	NZM4-XUHIV48DC-PI
Catalog number	189794
Category	Under voltage coil
Minimum order	1 Pcs
Document ID	EO-53DE31163B
Generated	2026-08-03

Product Overview

minimum voltage trigger for NZM4, 1 contact aux. forward, 2NO, 48DC, spring terminals

Optional accessories for the circuit-breaker series NZM offers a comprehensive portfolio of application options for use world wide. The mounting is always flexible and easy thanks to the modular function groups. Notes: Undervoltage releases with one early-make contact and push-in terminals. For interlocking and load-shedding circuits, as well as for early-make of the undervoltage release in main-switch applications. Non-delayed disconnection of circuit-breaker NZM when control voltage drops below 35 - 70 % Us. For use with emergency switching off devices in conjunction with emergency switching off button . When the undervoltage release is de-energized, accidental contact with the main contacts of the circuit-breaker during attempts to switch on is reliably prevented. Early-make of auxiliary contacts on switching on and off (manual operation): approx. 20 ms (NZM2/3) and 90 ms (NZM4). Undervoltage release modules cannot be installed simultaneously with early-make contact NZM...-XHIV, shunt release NZM...-XA... or relais modules NZM...-X2A...

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > Circuit Breakers NZM**

Additional Product Information

ETIM for 189794 Low-voltage industrial controls and switchgear (EC001022)

Feature Name

Feature Value

Rated control supply voltage AC 50 Hz (EF003978)

0 V

Rated control supply voltage AC 60 Hz (EF003979)

0 V

Rated control supply voltage DC (EF003980)

48 V

Voltage type for actuating (EF008242)

AC

Type of electric connection (EF003961)

Screw connection

Number of contacts as normally open contact (EF008256)

1

Number of contacts as normally closed contact (EF008255)

0

Number of contacts as change-over contact (EF008257)

0

Delayed (EF001541)

No

Suitable for power circuit breaker (EF005863)

No

Suitable for off-load switch (EF001543)

Yes

Suitable for motor safety switch (EF005826)

Yes

Suitable for overload relay (EF001545)

No

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / NZM4-XUHIV48DC-PI with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.