

INDUSTRIAL COMPONENT DATA

NZMC2-4-A300/200 107585 Y7-107585 EATON ELECTRIC
NZMC2-4-A300/200

Brand: EATON - MOELLER | Manufacturer Part Number: NZMC2-4-A300/200



Manufacturer	EATON - MOELLER
MPN / Reference	NZMC2-4-A300/200
Catalog number	Y7-107585
Category	Power circuit-breaker for trafo/generator/installation protection
Minimum order	1 Pcs
Document ID	EO-E359B81B57
Generated	2026-08-06

Product Overview

NZMC2-4-A300/200

Circuit-breaker, 4p, 300A, 200A in 4th pole

Circuit-breaker NZM2, 4 pole, Switching capacity 400/415 V 50 Hz(Icu): 36 kA, Rated current = rated uninterrupted current

Rated current = rated uninterrupted current(In = Iu): 300 A, Installation type: Fixed, Screw connection, Standard/Approval:

IEC, Protective function: System and cable protection

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Circuit Breakers NZM

Additional Product Information

Circuit-breaker, 4p, 300A, 200A in 4th poleCircuit-breaker NZM2, 4 pole, Switching capacity 400/415 V 50 Hz(Icu): 36 kA,

Rated current = rated uninterrupted current Rated current = rated uninterrupted current(In = Iu): 300 A, Installation type:

Fixed, Screw connection, Standard/Approval: IEC, Protective function: System and cable protection

General specificationsProduct nameEaton Moeller series NZM molded case circuit breaker thermo-magneticPart

no.NZMC2-4-A300/200EAN4015081072651Product Length/Depth149 millimetreProduct height184 millimetreProduct

width140 millimetreProduct weight3 kilogramCompliancesRoHS conformCertificationsIEC/EN 60947

IECProduct TradenameNZMProduct TypeMolded case circuit breakerProduct Sub TypeThermo-magneticDelivery

programApplicationUse in unearthed supply systems at 690 VTypeCircuit breakerCircuit breaker frame typeNZM2Number

of polesFour-poleAmperage Rating300 ARelease systemThermomagnetic releaseFeaturesMotor drive optional

Protection unitSpecial featuresMaximum back-up fuse, if the expected short-circuit currents at the installation location

exceed the switching capacity of the circuit breaker (Rated short-circuit breaking capacity Icn)

Rated current = rated uninterrupted current: 300 A

Reduced neutral conductor protection

Set value in neutral conductor is synchronous with set value I_r of main pole. Technical Data - Electrical Voltage rating 690 V - 690 V Rated insulation voltage (U_i) 690 V AC Rated impulse withstand voltage (U_{imp}) at auxiliary con...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / NZMC2-4-A300/200 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.