

INDUSTRIAL COMPONENT DATA

NZMC3-4-A400 109690 Y7-109690 EATON ELECTRIC
NZMC3-4-A400

Brand: EATON - MOELLER | Manufacturer Part Number: NZMC3-4-A400



Manufacturer	EATON - MOELLER
MPN / Reference	NZMC3-4-A400
Catalog number	Y7-109690
Category	Power circuit-breaker for trafo/generator/installation protection
Minimum order	1 Pcs
Document ID	EO-EF752AD3E2
Generated	2026-08-01

Product Overview

NZMC3-4-A400

Circuit-breaker, 4p, 400A

Circuit-breaker NZM3, 4 pole, Switching capacity 400/415 V 50 Hz(Icu): 36 kA, Rated current = rated uninterrupted current
Rated current = rated uninterrupted current(In = Iu): 400 A, Installation type: Fixed, Screw connection, Standard/Approval:
IEC, Protective function: System and cable protection

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Circuit Breakers NZM

Additional Product Information

Circuit-breaker, 4p, 400ACircuit-breaker NZM3, 4 pole, Switching capacity 400/415 V 50 Hz(Icu): 36 kA, Rated current =
rated uninterrupted current Rated current = rated uninterrupted current(In = Iu): 400 A, Installation type: Fixed, Screw
connection, Standard/Approval: IEC, Protective function: System and cable protection

General specificationsProduct nameEaton Moeller series NZM molded case circuit breaker thermo-magneticPart
no.NZMC3-4-A400EAN4015081092765Product Length/Depth166 millimetreProduct height275 millimetreProduct width185
millimetreProduct weight7.3 kilogramCompliancesRoHS conformCertificationsIEC

IEC/EN 60947Product TradenameNZMProduct TypeMolded case circuit breakerProduct Sub

TypeThermo-magneticDelivery programApplicationUse in unearthed supply systems at 690 VTypeCircuit breakerCircuit
breaker frame typeNZM3Number of polesFour-poleAmperage Rating400 ARelease systemThermomagnetic
releaseFeaturesMotor drive optional

Protection unitSpecial featuresMaximum back-up fuse, if the expected short-circuit currents at the installation location

exceed the switching capacity of the circuit breaker (Rated short-circuit breaking capacity I_{cn}) Rated current = rated uninterrupted current: 400 A Set value in neutral conductor is synchronous with set value I_r of main pole. Terminal capacity hint: Up to 240 mm² can be connected depending on the cable manufacturer. Technical Data - Electrical Voltage rating 690 V - 690 V Rated insulation voltage (U_i) 1000 V AC Rated impulse withstan...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / NZMC3-4-A400 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.