

INDUSTRIAL COMPONENT DATA

NZMH2-4-AX25 193363 EATON ELECTRIC Automatic Int. NZM2 PXR10, 25A, 4p, Screw Terminal

Brand: EATON - MOELLER | Manufacturer Part Number: NZMH2-4-AX25



Manufacturer	EATON - MOELLER
MPN / Reference	NZMH2-4-AX25
Catalog number	193363
Category	Power circuit-breaker for trafo/generator/installation protection
Minimum order	1 Pcs
Document ID	EO-9BDE883464
Generated	2026-08-05

Product Overview

Automatic Int. NZM2 PXR10, 25A, 4p, Screw Terminal

NZM2 PXR10 circuit breaker, 25A, 4p, Screw terminal

The NZM...-AX xEffect circuit breaker range with the power expert release (PXR) electronic triggering system covers use cases for system and cable protection with only four compact sizes and is suitable for the IEC market. Test function and settings via micro USB port directly on the switch. Modular function groups always make mounting flexible and may be supplemented by the comprehensive range of accessories. R.m.s. value measurement and thermal memory

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Circuit Breakers NZM
--------------	--

Additional Product Information

General specifications

Product Name Eaton Moeller series NZM molded case circuit breaker electronic Catalog Number 193363 Model Code NZMH2-4-AX25 EAN 9010238017085 Product Length/Depth 149 mm Product Height 184 mm Product Width 140 mm Product Weight 3 kg Compliances RoHS conform Certifications IEC/EN 60947

IEC Product specifications

Type Circuit breaker Special features Maximum back-up fuse, if the expected short-circuit currents at the installation location exceed the switching capacity of the circuit breaker (Rated short-circuit breaking capacity I_{cn}) Overload and short-circuit protection LIR.m.s. value measurement and "thermal memory" USB interface for configuration and test function with Power Xpert Protection Manager software Rated current = rated uninterrupted current: 25 A Amperage Rating 25 A Voltage rating 690 V - 690 V Circuit breaker frame type NZM2 Features Protection unit

Motor drive optional 10.10 Temperature rise The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices. 10.11 Short-circuit rating Is the panel builder's responsibility. The specifications for the switchgear must be observed. 10.12 Electromagnetic compatibility Is the panel builder's responsibility. The specifications for the switchgear must be observed. 10.13 Mechanical function The device meets the requirements, provided the information in the instruction leaflet (IL) is observed. 10.2.2 Corrosion resistance Meets the product s...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / NZMH2-4-AX25 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.