

INDUSTRIAL COMPONENT DATA

NZMH2-4-PX25/VAR-TZ 192054 EATON ELECTRIC NZM2 PXR25 Automatic Int. Class 1, 25A, 4p, Variable Power Reading..

Brand: EATON - MOELLER | Manufacturer Part Number: NZMH2-4-PX25/VAR-TZ



Manufacturer	EATON - MOELLER
MPN / Reference	NZMH2-4-PX25/VAR-TZ
Catalog number	192054
Category	Power circuit-breaker for trafo/generator/installation protection
Minimum order	1 Pcs
Document ID	EO-6EB310A0C9
Generated	2026-08-05

Product Overview

NZM2 PXR25 Automatic Int. - Class 1, 25A, 4p, Variable Power Reading, Screw Terminal, Ground Fault Protection and ZSI
NZM2 PXR25 circuit breaker - integrated energy measurement class 1, 25A, 4p, variable, Screw terminal, earth-fault protection and zone selectivity

The xEffect NZM...-PX...-TZ circuit breaker range with power expert release (PXR) electronic triggering system covers use cases for full range protection including grounding protection with only four compact sizes and is suitable for the IEC market. The integrated energy measuring function supplies currents, voltages and active energy (kWh) with accuracy class 1 according to IEC 61557-12. Zone selectivity for extended protection included. Test function and settings via micro USB port directly on the switch. Modular function groups always make mounting flexible and may be supplemented by the comprehensive range of accessories. R.m.s. value measurement and thermal memory

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Circuit Breakers NZM
--------------	--

Additional Product Information

General specifications

Product Name Eaton Moeller series NZM molded case circuit breaker electronic Catalog Number 192054 Model Code NZMH2-4-PX25/VAR-TZ EAN 4015081926053 Product Length/Depth 149 mm Product Height 184 mm Product Width 140 mm Product Weight 2.9 kg Certifications IEC/EN 60947

IEC Product specifications

Type Circuit breaker Special features LSIG overload protection and delayed and non-delayed short-circuit protective device, earth-fault protection Class 1 energy measurement, r.m.s. value measurement, and "thermal memory" USB interface for configuration and test function with Power Xpert Protection Manager software Zone selectivity ZSI Interface module in equipment supplied. Optionally communication-capable with internal Modbus RTU module or CAM Maximum back-up fuse, if the expected short-circuit currents at the installation location exceed the switching capacity of the circuit breaker (Rated short-circuit breaking capacity I_{cn}) Rated current = rated uninterrupted current: 25 A Application Use in unearthed supply systems at 690 V Amperage Rating 25 A Voltage rating 690 V - 690 V Circuit breaker frame type NZM2 Features Motor drive optional

Protection unit 10.10 Temperature rise The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices. 10.11 Short-circuit rating Is the panel builder's responsibility. The specifications for the switchgear must be observed. 10.12 Electromagnetic compatibility Is the pa...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / NZMH2-4-PX25/VAR-TZ with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.