

INDUSTRIAL COMPONENT DATA

NZMH2-4-PX40/VAR-TZ-SVE 192097 EATON ELECTRIC NZM2 PXR25 Auto Int. Class 1 Power Reading, 40A, 4p, Variable,..

Brand: EATON - MOELLER | Manufacturer Part Number: NZMH2-4-PX40/VAR-TZ-SVE



Manufacturer	EATON - MOELLER
MPN / Reference	NZMH2-4-PX40/VAR-TZ-SVE
Catalog number	192097
Category	Power circuit-breaker for trafo/generator/installation protection
Minimum order	1 Pcs
Document ID	EO-542B56C1A1
Generated	2026-08-06

Product Overview

NZM2 PXR25 Auto Int. - Class 1 Power Reading, 40A, 4p, Variable, Ground Fault Protection and ZSI, Plug-in Version
NZM2 PXR25 circuit breaker - integrated energy measurement class 1, 40A, 4p, variable, earth-fault protection and zone selectivity, plug-in technology

The xEffect NZM...-PX...-TZ circuit breaker range with power expert release (PXR) electronic triggering system covers use cases for full range protection including earth fault protection with only four compact sizes and is suitable for the IEC market. The integrated energy measuring function supplies currents, voltages and active energy (kWh) with accuracy class 1 according to IEC 61557-12. Zone selectivity for extended protection included. Test function and settings via micro USB port directly on the switch. Modular function groups always make mounting flexible and may be supplemented by the comprehensive range of accessories. R.m.s. value measurement and thermal memory.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Circuit Breakers NZM
--------------	--

Additional Product Information

NZM2 PXR25 circuit breaker - integrated energy measurement class 1, 40A, 4p, variable, earth-fault protection and zone selectivity, plug-in technology
The xEffect NZM...-PX...-TZ circuit breaker range with power expert release (PXR) electronic triggering system covers use cases for full range protection including earth fault protection with only four compact sizes and is suitable for the IEC market. The integrated energy measuring function supplies currents, voltages and active energy (kWh) with accuracy class 1 according to IEC 61557-12. Zone selectivity for extended protection included. Test function and settings via micro USB port directly on the switch. Modular function groups always make mounting flexible and may be supplemented by the comprehensive range of accessories. R.m.s. value measurement and thermal memory. Delivery

program

Product rangeCircuit-breakerProtective functionSystems, cable, selectivity and generator protection

Earth-fault protection

Zone selectivityStandard/ApprovalIECInstallation typePlug-in unitsRelease systemElectronic releaseConstruction

sizeNZM2DescriptionLSIG overload protection and delayed and non-delayed short-circuit protective device, earth-fault protection

Class 1 energy measurement, r.m.s. value measurement, and "thermal memory"

USB interface for configuration and test function with Power Xpert Protection Manager software

Zone selectivity ZSI

Interface module in equipment supplied.

Optionally communication-capable with internal Modbus RTU m...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / NZMH2-4-PX40/VAR-TZ-SVE with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.