

INDUSTRIAL COMPONENT DATA

NZMH2-AX63 192008 EATON ELECTRIC Automatic int. NZM2 PXR10, 3p, 63A, screw terminal

Brand: EATON - MOELLER | Manufacturer Part Number: NZMH2-AX63



Manufacturer	EATON - MOELLER
MPN / Reference	NZMH2-AX63
Catalog number	192008
Category	Power circuit-breaker for trafo/generator/installation protection
Minimum order	1 Pcs
Document ID	EO-77C5B2634C
Generated	2026-08-04

Product Overview

Automatic int. NZM2 PXR10, 3p, 63A, screw terminal

Circuit-breaker, NZM2 PXR10, 3 pole, 63A, screw terminal

The xEffect NZM...-AX circuit breaker range with the power expert release (PXR) electronic triggering system covers use cases for system and cable protection with only four compact sizes and is suitable for the IEC market. Test function and settings via micro USB port directly on the switch. Modular function groups always make mounting flexible and may be supplemented by the comprehensive range of accessories. R.m.s. value measurement and thermal memory

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Circuit Breakers NZM
--------------	--

Additional Product Information

Circuit-breaker, NZM2 PXR10, 3 pole, 63A, screw terminalThe xEffect NZM...-AX circuit breaker range with the power expert release (PXR) electronic triggering system covers use cases for system and cable protection with only four compact sizes and is suitable for the IEC market. Test function and settings via micro USB port directly on the switch. Modular function groups always make mounting flexible and may be supplemented by the comprehensive range of accessories.

R.m.s. value measurement and thermal memoryDelivery program

Product rangeCircuit-breakerProtective functionSystem and cable protectionStandard/ApprovalIECInstallation

typeFixedRelease systemElectronic releaseConstruction sizeNZM2DescriptionOverload and short-circuit protection LI

R.m.s. value measurement and "thermal memory"

USB interface for configuration and test function with Power Xpert Protection Manager softwareNumber of poles3

poleStandard equipmentScrew connectionRated current = rated uninterrupted current [In= Iu]Rated current = rated

uninterrupted current [$I_n = I_u$] 63 A Setting range Overload trip [I_r] 25 - 63 A Short-circuit releases [I_{rm}] Non-delayed [$I_i = I_{nx} \dots$] 2 - 12 Technical data

General Standards IEC/EN 60947 Protection against direct contact Finger and back of hand proof to VDE 0106 Part

100 Climatic proofing Damp heat, constant, to IEC 60068-2-78

Damp heat, cyclic, to IEC 60068-2-30 Ambient temperature Ambient temperature, storage - 40 - + 70 °C Ambient

temperature Operation -25 - +70 °C Mechanical shock resistance (10....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / NZMH2-AX63 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.