

INDUSTRIAL COMPONENT DATA

NZMH2-MX140-BT-NA 192466 EATON ELECTRIC Automatic int. NZM2 PXR20, 140A, 3p, terminals box, UL/CSA

Brand: EATON - MOELLER | Manufacturer Part Number: NZMH2-MX140-BT-NA



Manufacturer	EATON - MOELLER
MPN / Reference	NZMH2-MX140-BT-NA
Catalog number	Y7-192466
Category	Motor protection circuit-breaker
Minimum order	1 Pcs
Document ID	EO-35C9D4C04B
Generated	2026-08-06

Product Overview

Automatic int. NZM2 PXR20, 140A, 3p, terminals box, UL/CSA

The xEffect NZM...-MX-NA circuit breaker range with power expert release (PXR) electronic triggering system covers use cases for motor protection with only four compact sizes and is suitable for the IEC and UL/CSA market. Test function and settings via micro USB port directly on the switch. Modular function groups always make mounting flexible and may be supplemented by the comprehensive range of accessories. R.m.s. value measurement and thermal memory.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > Circuit Breakers NZM**

Additional Product Information

ETIM for 192466 Low-voltage industrial controls and switchgear (EC000074)

Feature Name

Feature Value

Overload release current setting (EF002336)

56 A

Adjustment range undelayed short-circuit release (EF007131)

280 A

With thermal overload protection (EF006233)

Yes

Phase failure sensitive (EF007400)

Yes

Switch off technique (EF007007)
Electronic
Rated operating voltage (EF001435)
690 V
Rated permanent current I_u (EF001389)
140 A
Rated operation power at AC-3, 230 V (EF007025)
45 kW
Rated operation power at AC-3, 400 V (EF001364)
75 kW
Type of electrical connection of main circuit (EF006819)
Other
Type of control element (EF006976)
Rocker lever
Device construction (EF008240)
Built-in device fixed built-in technique
With integrated auxiliary switch (EF001387)
No
With integrated under voltage release (EF001390)
No
Number of poles (EF001391)
3
Rated short-circuit breaking capacity I_{cu} at 400 V, AC (EF007049)
150 kA
Degree of protection (IP) (EF005474)
IP20
Height (EF000040)
195 mm
Width (EF000008)
105 mm
Depth (EF000049)
149 mm

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / NZMH2-MX140-BT-NA with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.