

INDUSTRIAL COMPONENT DATA

NZMH3-AX400-NA 192497 EATON ELECTRIC Automatic Int. NZM3 PXR10, 400A, 3p, Screw Terminals, UL/CSA

Brand: EATON - MOELLER | Manufacturer Part Number: NZMH3-AX400-NA



Manufacturer	EATON - MOELLER
MPN / Reference	NZMH3-AX400-NA
Catalog number	Y7-192497
Category	Power circuit-breaker for trafo/generator/installation protection
Minimum order	1 Pcs
Document ID	EO-F5B83177C3
Generated	2026-08-05

Product Overview

Automatic Int. NZM3 PXR10, 400A, 3p, Screw Terminals, UL/CSA

NZM3 PXR10 circuit breaker, 400A, 3p, Screw terminal, UL/CSA

The xEffect NZM...-AX-NA circuit breaker range with power expert release (PXR) electronic triggering system covers use cases for system and cable protection with only four compact sizes and is suitable for the IEC and UL/CSA market. Test function and settings via micro USB port directly on the switch. Modular function groups always make mounting flexible and may be supplemented by the comprehensive range of accessories. R.m.s. value measurement and thermal memory.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > Circuit Breakers NZM**

Additional Product Information

General specifications

Product Name Eaton Moeller series NZM molded case circuit breaker electronic Catalog Number 192497 Model Code NZMH3-AX400-NA EAN 4015081932252 Product Length/Depth 166 mm Product Height 297 mm Product Width 140 mm Product Weight 7.021 kg Compliances RoHS conform Certifications IEC 60947-2

Specially designed for North America

UL/CSA

CSA (Class No. 1432-01)

UL (Category Control Number DIVQ)

CSA certified

CSA-C22.2 No. 5-09

CSA (File No. 22086)

UL 489

IEC

UL listed

UL (File No. E31593)

CE marking Product specifications

Type Special features Circuit breaker Application Branch circuits, feeder circuits Amperage Rating 400 A Voltage rating 690 V - 690 V Circuit breaker frame type NZM3 Features Motor drive optional

Protection unit 10.10 Temperature rise The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices. 10.11 Short-circuit rating Is the panel builder's responsibility. The specifications for the switchgear must be observed. 10.12 Electromagnetic compatibility Is the panel builder's responsibility. The specifications for the switchgear must be observed. 10.13 Mechanical function The device meets the requirements, provided the information in the instruction leaflet (IL) is observed. 10.2.2 Corrosion resistance Meets the product standard's requirements. 10.2.3.1 Verification of thermal stability of enclosures Meets the product standard's requirements. 10.2.3.2 Verification of resistance...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / NZMH3-AX400-NA with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.