

INDUSTRIAL COMPONENT DATA

NZMH3-MX250-NA 193347 Y7-193347 EATON ELECTRIC Automatic Int. NZM3 PXR20, 250A, 3p, Screw Terminals, UL/CSA

Brand: EATON - MOELLER | Manufacturer Part Number: NZMH3-MX250-NA



Manufacturer	EATON - MOELLER
MPN / Reference	NZMH3-MX250-NA
Catalog number	Y7-193347
Category	Motor protection circuit-breaker
Minimum order	1 Pcs
Document ID	EO-9C2A75BF0E
Generated	2026-08-06

Product Overview

Automatic Int. NZM3 PXR20, 250A, 3p, Screw Terminals, UL/CSA

NZMH3-MX250-NA. NZM3 PXR20 circuit breaker, 250A, 3p, Screw terminal, UL/CSA

The xEffect NZM...-MX-NA circuit breaker range with power expert release (PXR) electronic triggering system covers use cases for motor protection with only four compact sizes and is suitable for the IEC and UL/CSA market. Test function and settings via micro USB port directly on the switch. Modular function groups always make mounting flexible and may be supplemented by the comprehensive range of accessories. R.m.s. value measurement and thermal memory.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Circuit Breakers NZM
--------------	--

Additional Product Information

General specifications

Product Name Eaton Moeller series NZM molded case circuit breaker electronic Catalog Number 193347 Model Code NZMH3-MX250-NA EAN 9010238016927 Product Length/Depth 166 mm Product Height 275 mm Product Width 140 mm Product Weight 7.054 kg Compliances RoHS conform Certifications CSA (Class No. 1432-01)

UL (File No. E31593)

UL 489

CE marking

IEC

UL508

CSA-C22.2 No. 5-09

CSA certified

IEC/EN 60947

UL listed

CSA (File No. 22086)

Specially designed for North America

IEC 60947-2

UL/CSA

UL (Category Control Number DIVQ) Product specifications

Type Circuit breaker Special features Maximum back-up fuse, if the expected short-circuit currents at the installation location exceed the switching capacity of the circuit breaker (Rated short-circuit breaking capacity I_{cn}) Motor protection - overload- and short-circuit protective device LI MotorPhase loss protection, r.m.s. value measurement, and "thermal memory" USB interface for configuration and test function with Power Xpert Protection Manager software Optionally communication-capable with interface module and internal Modbus RTU module or CAM Switches conform to UL/CSA as well as the IEC regulations. IEC switching performance values are contained on the rating plate. Rated current = rated uninterrupted current: 250 A Application Branch circuits, feeder circuits Amperage Rating 250 A Voltage rating 690 V - 690 V Circuit breaker frame type NZM3 10.10 Temperature rise The panel builder is responsible for the temperature ri...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / NZMH3-MX250-NA with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.