

INDUSTRIAL COMPONENT DATA

NZMH3-PMX350-NA 193354 Y7-193354 EATON ELECTRIC Int. Auto NZM3 PXR25, 350A, 3p, Screw Terminal, UL/CSA

Brand: EATON - MOELLER | Manufacturer Part Number: NZMH3-PMX350-NA



Manufacturer	EATON - MOELLER
MPN / Reference	NZMH3-PMX350-NA
Catalog number	Y7-193354
Category	Motor protection circuit-breaker
Minimum order	1 Pcs
Document ID	EO-9C8D445A5E
Generated	2026-08-05

Product Overview

Int. Auto NZM3 PXR25, 350A, 3p, Screw Terminal, UL/CSA

NZMH3-PMX350-NA. NZM3 PXR25 circuit breaker, 350A, 3p, Screw terminal, UL/CSA

The xEffect NZM...-PMX-NA circuit breaker range with power expert release (PXR) electronic triggering system covers use cases for motor protection with only four compact sizes and is suitable for the IEC market. The integrated energy measuring function supplies currents, voltages and active energy (kWh) with accuracy class 1 according to IEC 61557-12. Test function and settings via micro USB port directly on the switch. Modular function groups always make mounting flexible and may be supplemented by the comprehensive range of accessories. R.m.s. value measurement and thermal memory.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Circuit Breakers NZM
--------------	--

Additional Product Information

General specifications

Product Name Eaton Moeller series NZM molded case circuit breaker electronic Catalog Number 193354 Model Code NZMH3-PMX350-NA EAN 9010238016996 Product Length/Depth 166 mm Product Height 275 mm Product Width 140 mm Product Weight 7.054 kg Certifications CSA certified

IEC/EN 60947

UL listed

IEC

UL (File No. E31593)

IEC 60947-2

UL 489

CSA-C22.2 No. 5-09

UL/CSA

CSA (File No. 22086)

UL (Category Control Number DIVQ)

CE marking

UL508

Specially designed for North America

CSA (Class No. 1432-01) Product specifications

Type Circuit breaker Special features Application Branch circuits, feeder circuits Amperage Rating 350 A Voltage rating 690 V - 690 V Circuit breaker frame type NZM3 10.10 Temperature rise The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices. 10.11 Short-circuit rating Is the panel builder's responsibility. The specifications for the switchgear must be observed. 10.12 Electromagnetic compatibility Is the panel builder's responsibility. The specifications for the switchgear must be observed. 10.13 Mechanical function The device meets the requirements, provided the information in the instruction leaflet (IL) is observed. 10.2.2 Corrosion resistance Meets the product standard's requirements. 10.2.3.1 Verification of thermal stability of enclosures Meets the product standard's requirements. 10.2.3.2 Verification of resistance of insulating materials to normal heat Meets the p...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / NZMH3-PMX350-NA with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.