

INDUSTRIAL COMPONENT DATA

NZMH3-PX400-NA 192590 Y7-192590 EATON ELECTRIC Automatic Int. NZM3 PXR25, 400A, 3p, Screw Terminal, UL/CSA

Brand: EATON - MOELLER | Manufacturer Part Number: NZMH3-PX400-NA



Manufacturer	EATON - MOELLER
MPN / Reference	NZMH3-PX400-NA
Catalog number	Y7-192590
Category	Power circuit-breaker for trafo/generator/installation protection
Minimum order	1 Pcs
Document ID	EO-EEC2C44A3D
Generated	2026-08-04

Product Overview

Automatic Int. NZM3 PXR25, 400A, 3p, Screw Terminal, UL/CSA

NZMH3 PXR25 circuit breaker, 400 A, 3-pole, Screw terminal, UL/CSA

The xEffect NZM...-PX-NA circuit breaker range with power expert release (PXR) electronic triggering system covers use cases for full range protection with only four compact sizes and is suitable for the IEC and UL/CSA market. The integrated energy measuring function supplies currents, voltages and active energy (kWh) with accuracy class 1 according to IEC 61557-12. Test function and settings via micro USB port directly on the switch. Modular function groups always make mounting flexible and may be supplemented by the comprehensive range of accessories. R.m.s. value measurement and thermal memory.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Circuit Breakers NZM
--------------	--

Additional Product Information

NZMH3 PXR25 circuit breaker, 400 A, 3-pole, Screw terminal, UL/CSA
NZMH3 PXR25 circuit breaker, Amperage rating: 400 A, Poles: 3, Electrical connection type: Screw connection, Degree of protection: IP20, Handle: Rocker lever, UL/CSA
General specifications
Product name Eaton Moeller series NZM molded case circuit breaker electronic
Part no. NZMH3-PX400-NA
EAN 4015081933181
Product Length/Depth 166 millimetre
Product height 297 millimetre
Product width 140 millimetre
Product weight 6.34 kilogram
Compliances RoHS conform
Certifications UL listed
CSA-C22.2 No. 5-09

CE marking

UL (Category Control Number DIVQ)

IEC 60947-2

UL/CSA

IEC/EN 60947

CSA (File No. 22086)

CSA certified

Specially designed for North America

IEC

CSA (Class No. 1432-01)

UL 489

UL (File No. E31593)Product TradenameNZMProduct TypeMolded case circuit breakerProduct Sub TypeElectronicDelivery programApplicationBranch circuits, feeder circuitsTypeMaximum back-up fuse, if the expected short-circuit currents at the installation location exceed the switching capacity of the circuit breaker (Rated short-circuit breaking capacity Icn)

Rated current = rated uninterrupted current: 400 A

Switches conform to UL/CSA as well as the IEC regulations. IEC switching performance values are contained on the rating plate.Circuit breaker frame typeNZM3Number of polesThree-poleAmperage Rating400 ARelease systemElectronic releaseFeaturesMotor drive optional

Protection unitSpecial featuresCircuit breakerTechnical Data - ElectricalVoltage rating690 V - 690...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / NZMH3-PX400-NA with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.