

INDUSTRIAL COMPONENT DATA

NZML2-MX140-SVE 191563 EATON ELECTRIC Automatic int. NZM2 PXR20, 140A, 3p, plug-in version

Brand: EATON - MOELLER | Manufacturer Part Number: NZML2-MX140-SVE



Manufacturer	EATON - MOELLER
MPN / Reference	NZML2-MX140-SVE
Catalog number	191563
Category	Motor protection circuit-breaker
Minimum order	1 Pcs
Document ID	EO-5DCABC5A04
Generated	2026-08-04

Product Overview

Automatic int. NZM2 PXR20, 140A, 3p, plug-in version

The xEffect NZM...-MX circuit breaker range with power expert release (PXR) electronic triggering system covers use cases for motor protection with only four compact sizes and is suitable for the IEC market. Test function and settings via micro USB port directly on the switch. Modular function groups always make mounting flexible and may be supplemented by the comprehensive range of accessories. R.m.s. value measurement and thermal memory

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > Circuit Breakers NZM**

Additional Product Information

ETIM for 191563 Low-voltage industrial controls and switchgear (EC000074)

Feature Name

Feature Value

Overload release current setting (EF002336)

56 A

Adjustment range undelayed short-circuit release (EF007131)

2 A

With thermal overload protection (EF006233)

true

Phase failure sensitive (EF007400)

true

Switch off technique (EF007007)
Electronic
Rated operating voltage (EF001435)
690 V
Rated permanent current I_u (EF001389)
140 A
Rated operation power at AC-3, 230 V (EF007025)
37 kW
Rated operation power at AC-3, 400 V (EF001364)
75 kW
Power loss (EF005387)
None W
Type of electrical connection of main circuit (EF006819)
Other
Type of control element (EF006976)
Rocker lever
Device construction (EF008240)
Built-in device plug-in technique
With integrated auxiliary switch (EF001387)
false
With integrated under voltage release (EF001390)
false
Number of poles (EF001391)
3
Rated short-circuit breaking capacity I_{cu} at 400 V, AC (EF007049)
130 kA
Degree of protection (IP) (EF005474)
IP20
Height (EF000040)
245 mm
Width (EF000008)
105 mm
Depth (EF000049)
180 mm

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / NZML2-MX140-SVE with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.