

INDUSTRIAL COMPONENT DATA

NZML3-MX220-AVE 191401 EATON ELECTRIC Automatic int. NZM3 PXR20, 220A, 3p, plug-in version

Brand: EATON - MOELLER | Manufacturer Part Number: NZML3-MX220-AVE



Manufacturer	EATON - MOELLER
MPN / Reference	NZML3-MX220-AVE
Catalog number	191401
Category	Motor protection circuit-breaker
Minimum order	1 Pcs
Document ID	EO-9155E74D23
Generated	2026-08-04

Product Overview

Automatic int. NZM3 PXR20, 220A, 3p, plug-in version

The xEffect NZM...-MX circuit breaker range with Power Expert Release (PXR) electronic triggering system covers a full range of protection applications with only four compact sizes and is suitable for the IEC market. Test function and settings via micro USB port directly on the switch. Modular function groups always make mounting flexible and may be supplemented by the comprehensive range of accessories. RMS value measurement and thermal memory

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > Circuit Breakers NZM**

Additional Product Information

ETIM for 191401 Low-voltage industrial controls and switchgear (EC000074)

Feature Name

Feature Value

Overload release current setting (EF002336)

88 A

Adjustment range undelayed short-circuit release (EF007131)

2 A

With thermal overload protection (EF006233)

Yes

Phase failure sensitive (EF007400)

Yes

Switch off technique (EF007007)
Electronic
Rated operating voltage (EF001435)
690 V
Rated permanent current I_u (EF001389)
220 A
Rated operation power at AC-3, 230 V (EF007025)
55 kW
Rated operation power at AC-3, 400 V (EF001364)
110 kW
Type of electrical connection of main circuit (EF006819)
Other
Type of control element (EF006976)
Rocker lever
Device construction (EF008240)
Built-in device slide-in technique (withdrawable)
With integrated auxiliary switch (EF001387)
No
With integrated under voltage release (EF001390)
No
Number of poles (EF001391)
3
Rated short-circuit breaking capacity I_{cu} at 400 V, AC (EF007049)
130 kA
Degree of protection (IP) (EF005474)
IP20
Height (EF000040)
346 mm
Width (EF000008)
185 mm
Depth (EF000049)
260 mm

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / NZML3-MX220-AVE with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.