

**INDUSTRIAL COMPONENT DATA**

# NZML3-VX400-AVE 191400 EATON ELECTRIC Automatic input NZM3 PXR20, 400A, 3p, plug-in version

Brand: EATON - MOELLER | Manufacturer Part Number: NZML3-VX400-AVE



|                 |                                                                   |
|-----------------|-------------------------------------------------------------------|
| Manufacturer    | EATON - MOELLER                                                   |
| MPN / Reference | NZML3-VX400-AVE                                                   |
| Catalog number  | 191400                                                            |
| Category        | Power circuit-breaker for trafo/generator/installation protection |
| Minimum order   | 1 Pcs                                                             |
| Document ID     | EO-76FBD13271                                                     |
| Generated       | 2026-08-03                                                        |

## Product Overview

Automatic input NZM3 PXR20, 400A, 3p, plug-in version

The xEffect NZM...-VX circuit breaker range with Power Expert Release (PXR) electronic triggering system covers a full range of protection applications with only four compact sizes and is suitable for the IEC market. Test function and settings via micro USB port directly on the switch. Modular function groups always make mounting flexible and may be supplemented by the comprehensive range of accessories. RMS value measurement and thermal memory

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path **EATON - MOELLER > Circuit Breakers NZM**

## Additional Product Information

ETIM for 191400 Low-voltage industrial controls and switchgear (EC000228)

Feature Name

Feature Value

Rated permanent current I<sub>u</sub> (EF001389)

400 A

Rated voltage (EF003977)

690 V

Rated short-circuit breaking capacity I<sub>cu</sub> at 400 V, 50 Hz (EF007048)

150 kA

Overload release current setting (EF002336)

160 A

Adjustment range short-term delayed short-circuit release (EF007129)

2 A

Adjustment range undelayed short-circuit release (EF007131)

2 A

Device construction (EF008240)

Built-in device slide-in technique (withdrawable)

Integrated earth fault protection (EF007296)

No

Type of electrical connection of main circuit (EF006819)

Other

Suitable for DIN rail (top hat rail) mounting (EF007250)

No

DIN rail (top hat rail) mounting optional (EF008904)

No

Number of auxiliary contacts as normally closed contact (EF001377)

0

Number of auxiliary contacts as normally open contact (EF001376)

0

Number of auxiliary contacts as change-over contact (EF003531)

0

With switched-off indicator (EF007006)

No

With integrated under voltage release (EF001390)

No

Number of poles (EF001391)

3

Position of connection for main current circuit (EF006671)

Front

Type of control element (EF006976)

Rocker lever

Complete device with protection unit (EF008906)

Yes

Motor drive integrated (EF006697)

No

Motor drive optional (EF007386)

Yes

Degree of protection (IP) (EF005474)

IP20

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / NZML3-VX400-AVE with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.