

INDUSTRIAL COMPONENT DATA

NZML4-MX875 191329 EATON ELECTRIC Automatic Int. NZM4 PXR20, 875A, 3p, Screw Terminals

Brand: EATON - MOELLER | Manufacturer Part Number: NZML4-MX875



Manufacturer	EATON - MOELLER
MPN / Reference	NZML4-MX875
Catalog number	191329
Category	Motor protection circuit-breaker
Minimum order	1 Pcs
Document ID	EO-0F34DC2A75
Generated	2026-08-05

Product Overview

Automatic Int. NZM4 PXR20, 875A, 3p, Screw Terminals

The xEffect NZM...-MX circuit breaker range with Power Expert Release (PXR) electronic triggering system covers all motor protection applications with only four compact sizes and is suitable for the IEC market. Test function and settings via micro USB port directly on the switch. Modular function groups always make mounting flexible and may be supplemented by the comprehensive range of accessories. R.m.s. value measurement and thermal memory

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Circuit Breakers NZM

Additional Product Information

ETIM for 191329 Low-voltage industrial controls and switchgear (EC000074)

Feature Name

Feature Value

Overload release current setting (EF002336)

438 A

Adjustment range undelayed short-circuit release (EF007131)

2 A

With thermal overload protection (EF006233)

Yes

Phase failure sensitive (EF007400)

Yes

Switch off technique (EF007007)
Electronic
Rated operating voltage (EF001435)
690 V
Rated operation power at AC-3, 230 V (EF007025)
250 kW
Rated operation power at AC-3, 400 V (EF001364)
500 kW
Type of electrical connection of main circuit (EF006819)
Screw connection
Type of control element (EF006976)
Rocker lever
Device construction (EF008240)
Built-in device fixed built-in technique
With integrated auxiliary switch (EF001387)
No
With integrated under voltage release (EF001390)
No
Number of poles (EF001391)
4
Rated short-circuit breaking capacity Icu at 400 V, AC (EF007049)
50 kA
Degree of protection (IP) (EF005474)
IP20
Height (EF000040)
207 mm
Width (EF000008)
210 mm
Depth (EF000049)
401 mm

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / NZML4-MX875 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.