

INDUSTRIAL COMPONENT DATA

NZMN2-4-VX40-T 193299 EATON ELECTRIC Automatic int. NZM2 PXR20, 40A, 4p, screw terminal, ground protection

Brand: EATON - MOELLER | Manufacturer Part Number: NZMN2-4-VX40-T



Manufacturer	EATON - MOELLER
MPN / Reference	NZMN2-4-VX40-T
Catalog number	193299
Category	Power circuit-breaker for trafo/generator/installation protection
Minimum order	1 Pcs
Document ID	EO-30A4BDDA65
Generated	2026-08-06

Product Overview

Automatic int. NZM2 PXR20, 40A, 4p, screw terminal, ground protection

NZM2 PXR20 circuit breaker, 40A, 4p, Screw terminal, earth-fault protection

The xEffect NZM...-VX circuit breaker range with power expert release (PXR) electronic triggering system covers use cases for full range protection with only four compact sizes and is suitable for the IEC market. Test function and settings via micro USB port directly on the switch. Modular function groups always make mounting flexible and may be supplemented by the comprehensive range of accessories. R.m.s. value measurement and thermal memory.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Circuit Breakers NZM
--------------	--

Additional Product Information

NZM2 PXR20 circuit breaker, 40A, 4p, Screw terminal, earth-fault protectionThe xEffect NZM...-VX circuit breaker range with power expert release (PXR) electronic triggering system covers use cases for full range protection with only four compact sizes and is suitable for the IEC market. Test function and settings via micro USB port directly on the switch. Modular function groups always make mounting flexible and may be supplemented by the comprehensive range of accessories. R.m.s. value measurement and thermal memory.Delivery program

Product rangeCircuit-breakerProtective functionSystems, cable, selectivity and generator protection

Earth-fault protectionStandard/ApprovalIECInstallation typeFixedRelease systemElectronic releaseConstruction sizeNZM2DescriptionLSI overload protection and delayed and non-delayed short-circuit protective device

R.m.s. value measurement and "thermal memory"

USB interface for configuration and test function with Power Xpert Protection Manager software

Optionally communication-capable with interface module and internal Modbus RTU module or CAM
Number of poles4
poleStandard equipmentScrew connectionSwitching capacity400/415 V 50 Hz [Icu]50 kARated current = rated uninterrupted
current [In= Iu]Rated current = rated uninterrupted current [In= Iu]40 ANeutral conductor [% of phase conductor]100
%Setting rangeOverload trip[Ir]20 - 40 AShort-circuit releases[Irm]Non-delayed[Ili= Inx ...]2 - 18Short-circuit
releases[Irm]Delayed[Ild= Irx ...]2 - 10Setting range of...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / NZMN2-4-VX40-T with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.