

INDUSTRIAL COMPONENT DATA

NZMN2-PMX40-SVE 192116 EATON ELECTRIC NZM2 PXR25 Auto Int. Class 1, 40A, 3p Power Reading, Plug-in Version

Brand: EATON - MOELLER | Manufacturer Part Number: NZMN2-PMX40-SVE



Manufacturer	EATON - MOELLER
MPN / Reference	NZMN2-PMX40-SVE
Catalog number	192116
Category	Motor protection circuit-breaker
Minimum order	1 Pcs
Document ID	EO-9C347BEBFF
Generated	2026-08-06

Product Overview

NZM2 PXR25 Auto Int. - Class 1, 40A, 3p Power Reading, Plug-in Version

NZM2 PXR25 circuit breaker - integrated energy measurement class 1, 40A, 3p, plug-in technology

The xEffect NZM...-PMX circuit breaker range with power expert release (PXR) electronic triggering system covers use cases for motor protection with only four compact sizes and is suitable for the IEC market. The integrated energy measuring function supplies currents, voltages and active energy (kWh) with accuracy class 1 according to IEC 61557-12. Test function and settings via micro USB port directly on the switch. Modular function groups always make mounting flexible and may be supplemented by the comprehensive range of accessories. R.m.s. value measurement and thermal memory.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Circuit Breakers NZM
--------------	--

Additional Product Information

NZM2 PXR25 circuit breaker - integrated energy measurement class 1, 40A, 3p, plug-in technologyThe xEffect NZM...-PMX circuit breaker range with power expert release (PXR) electronic triggering system covers use cases for motor protection with only four compact sizes and is suitable for the IEC market. The integrated energy measuring function supplies currents, voltages and active energy (kWh) with accuracy class 1 according to IEC 61557-12. Test function and settings via micro USB port directly on the switch. Modular function groups always make mounting flexible and may be supplemented by the comprehensive range of accessories. R.m.s. value measurement and thermal memory.Delivery program
Product rangeCircuit-breakerProtective functionMotor protectionStandard/ApprovalIECInstallation typePlug-in unitsRelease systemElectronic releaseConstruction sizeNZM2DescriptionMotor protection - overload- and short-circuit protective device LI Motor

Class 1 energy measurement, phase loss protection, r.m.s. value measurement, and "thermal memory"

USB interface for configuration and test function with Power Xpert Protection Manager software

Interface module in equipment supplied.

Optionally communication-capable with interface module and internal Modbus RTU module or CAN

Number of poles 3
Standard equipment Screw connection Switching capacity 400/415 V 50 Hz [Icu] 50 kA Rated current = rated uninterrupted
current [In = Iu] 40 A Setting range Overload trip [Ir] 20 - 40 A Short-circuit releases [Irm] Non-...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / NZMN2-PMX40-SVE with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.