

INDUSTRIAL COMPONENT DATA

NZMN3-PMX250-NA 193350 Y7-193350 EATON ELECTRIC Automatic Int. NZM3 PXR25, 250A, 3p, Screw Terminal, UL/CSA

Brand: EATON - MOELLER | Manufacturer Part Number: NZMN3-PMX250-NA



Manufacturer	EATON - MOELLER
MPN / Reference	NZMN3-PMX250-NA
Catalog number	Y7-193350
Category	Motor protection circuit-breaker
Minimum order	1 Pcs
Document ID	EO-21978768BA
Generated	2026-08-05

Product Overview

Automatic Int. NZM3 PXR25, 250A, 3p, Screw Terminal, UL/CSA

NZMN3-PMX250-NA. NZM3 PXR25 circuit breaker, 250A, 3p, Screw terminal, UL/CSA

The xEffect NZM...-PMX-NA circuit breaker range with power expert release (PXR) electronic triggering system covers use cases for motor protection with only four compact sizes and is suitable for the IEC market. The integrated energy measuring function supplies currents, voltages and active energy (kWh) with accuracy class 1 according to IEC 61557-12. Test function and settings via micro USB port directly on the switch. Modular function groups always make mounting flexible and may be supplemented by the comprehensive range of accessories. R.m.s. value measurement and thermal memory.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > Circuit Breakers NZM**

Additional Product Information

General specifications

Product Name Eaton Moeller series NZM molded case circuit breaker electronic Catalog Number 193350 Model Code NZMN3-PMX250-NA EAN 9010238016958 Product Length/Depth 166 mm Product Height 275 mm Product Width 140 mm Product Weight 7.054 kg Certifications CSA (Class No. 1432-01)

IEC 60947-2

CE marking

UL (Category Control Number DIVQ)

UL listed

CSA-C22.2 No. 5-09

UL508

CSA (File No. 22086)

UL 489

IEC/EN 60947

UL/CSA

CSA certified

Specially designed for North America

IEC

UL (File No. E31593) Product specifications

Type Circuit breaker Special features Application Branch circuits, feeder circuits

Use in unearthed supply systems at 690 V

Amperage Rating 250 A Voltage rating 690 V - 690 V Circuit breaker frame type NZM3 10.10 Temperature rise The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices. 10.11

Short-circuit rating Is the panel builder's responsibility. The specifications for the switchgear must be observed. 10.12

Electromagnetic compatibility Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.13 Mechanical function The device meets the requirements, provided the information in the instruction leaflet (IL) is

observed. 10.2.2 Corrosion resistance Meets the product standard's requirements. 10.2.3.1 Verification of thermal stability

of enclosures Meets the product standard's requirements. 10.2.3.2 Verification of resistance of insula...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / NZMN3-PMX250-NA with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.