

INDUSTRIAL COMPONENT DATA

NZMS2-4-A160/100-SVE 113315 Y7-113315 EATON ELECTRIC NZMS2-4-A160/100-SVE

Brand: EATON - MOELLER | Manufacturer Part Number: NZMS2-4-A160/100-SVE



Manufacturer	EATON - MOELLER
MPN / Reference	NZMS2-4-A160/100-SVE
Catalog number	Y7-113315
Category	Power circuit-breaker for trafo/generator/installation protection
Minimum order	1 Pcs
Document ID	EO-B66A36AE8F
Generated	2026-08-05

Product Overview

NZMS2-4-A160/100-SVE

NZMS2-4-A160/100-SVE. Circuit breaker 4-pole 160A, system/cable protection, withdrawable unit

Series NZM...A circuit-breakers cover all application cases with just four compact sizes and are suitable for the IEC market.

Modular function groups always make mounting flexible. With thermomagnetic releases for systems and cable protection.

Notes: set value in neutral conductor is synchronous with set value Ir of phase conductor.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Circuit Breakers NZM

Additional Product Information

General Specifications

Product Name Eaton Moeller series NZM molded case circuit breaker thermo-magnetic Catalog Number 113315 Ean 4015081128501 Product Length/Depth 180 mm Product Height 245 mm Product Width 140 mm Product Weight 4.07 kg
Compliances RoHS conform Model Code NZMS2-4-A160/100-SVE Technical Data - Electrical

Voltage rating 690 V - 690 V Current rating of neutral conductor 60% of phase conductor Amperage Rating 160 A
Instantaneous current setting (Ii) - min 6 A Instantaneous current setting (Ii) - max 10 A Overload current setting (Ir) 80 A - 100 A Overload current setting (Ir) - min 125 A Overload current setting (Ir) - max 160 A Short delay current setting (Isd) - min 0 A Short delay current setting (Isd) - max 0 A Short-circuit release non-delayed setting - min 6 A Short-circuit release non-delayed setting - max 10 A Rated short-circuit breaking capacity Ics (IEC/EN 60947) at 400/415 V, 50/60 Hz 70 kA
Electrical connection type of main circuit Screw connection Handle type Rocker lever Overvoltage category Iii Pollution degree 3 Technical data - communication

Current rating of neutral conductor 60% of phase conductor Amperage Rating 160 A Instantaneous current setting (Ii) - min 6 A Instantaneous current setting (Ii) - max 10 A Overload current setting (Ir) 80 A - 100 A Overload current setting (Ir) - min 125 A Overload current setting (Ir) - max 160 A Short delay current setting (Isd) - min 0 A Short delay current setting (Isd) - max 0 A Short-circuit release...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / NZMS2-4-A160/100-SVE with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.