

INDUSTRIAL COMPONENT DATA

NZMS2-4-A160-SVE 113314 Y7-113314 EATON ELECTRIC NZMS2-4-A160-SVE

Brand: EATON - MOELLER | Manufacturer Part Number: NZMS2-4-A160-SVE



Manufacturer	EATON - MOELLER
MPN / Reference	NZMS2-4-A160-SVE
Catalog number	Y7-113314
Category	Power circuit-breaker for trafo/generator/installation protection
Minimum order	1 Pcs
Document ID	EO-7A54B105E4
Generated	2026-08-05

Product Overview

NZMS2-4-A160-SVE

Circuit breaker 4-pole 160A, system/cable protection, withdrawable unit

Series NZM...-A circuit-breakers cover all application cases with just four compact sizes and are suitable for the IEC market. Modular function groups always make mounting flexible. With thermomagnetic releases for systems and cable protection.

Notes: set value in neutral conductor is synchronous with set value I_r of phase conductor.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Circuit Breakers NZM

Additional Product Information

Circuit breaker 4-pole 160A, system/cable protection, withdrawable unit Series NZM...-A circuit-breakers cover all application cases with just four compact sizes and are suitable for the IEC market. Modular function groups always make mounting flexible. With thermomagnetic releases for systems and cable protection. Notes: set value in neutral conductor is synchronous with set value I_r of phase conductor.

General specifications
Product name Eaton Moeller series NZM molded case circuit breaker thermo-magnetic
Part no. NZMS2-4-A160-SVE
EAN 4015081128495
Product Length/Depth 180 millimetre
Product height 245 millimetre
Product width 140 millimetre
Product weight 4.07 kilogram
Compliance RoHS conform
Product Tradename NZM
Product Type Molded case circuit breaker
Product Sub Type Thermo-magnetic
Delivery program Number of poles Four-pole
Amperage Rating 160 A
Features Protection unit

Motor drive optional
Special features Rated current = rated uninterrupted current: 160 A
Technical Data - Electrical
Voltage rating 690 V - 690 V
Current rating of neutral conductor 100% of phase conductor
Instantaneous current setting (li) - min 6

Instantaneous current setting (Ii) - max10 A
Overload current setting (Ir)125 A - 160 A
Overload current setting (Ir) - min125 A
Overload current setting (Ir) - max160 A
Short delay current setting (Isd) - min0 A
Short delay current setting (Isd) - max0 A
Short-circuit release non-delayed setting - min6 A
Short-circuit release non-delayed setting - max10 A
Rated short-circuit breaking capacity Ics (IEC...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / NZMS2-4-A160-SVE with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.