

## INDUSTRIAL COMPONENT DATA

# NZMS2-4-AX25 193370 EATON ELECTRIC Automatic Int. NZM2 PXR10, 25A, 4p, Screw Terminal

Brand: EATON - MOELLER | Manufacturer Part Number: NZMS2-4-AX25



|                 |                                                                   |
|-----------------|-------------------------------------------------------------------|
| Manufacturer    | EATON - MOELLER                                                   |
| MPN / Reference | NZMS2-4-AX25                                                      |
| Catalog number  | 193370                                                            |
| Category        | Power circuit-breaker for trafo/generator/installation protection |
| Minimum order   | 1 Pcs                                                             |
| Document ID     | EO-EFBFC115D3                                                     |
| Generated       | 2026-08-04                                                        |

## Product Overview

Automatic Int. NZM2 PXR10, 25A, 4p, Screw Terminal

NZM2 PXR10 circuit breaker, 25A, 4p, Screw terminal

The NZM...-AX xEffect circuit breaker range with the power expert release (PXR) electronic triggering system covers use cases for system and cable protection with only four compact sizes and is suitable for the IEC market. Test function and settings via micro USB port directly on the switch. Modular function groups always make mounting flexible and may be supplemented by the comprehensive range of accessories. R.m.s. value measurement and thermal memory

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                                        |
|--------------|----------------------------------------|
| Catalog path | EATON - MOELLER > Circuit Breakers NZM |
|--------------|----------------------------------------|

## Additional Product Information

NZM2 PXR10 circuit breaker, 25A, 4p, Screw terminalThe NZM...-AX xEffect circuit breaker range with the power expert release (PXR) electronic triggering system covers use cases for system and cable protection with only four compact sizes and is suitable for the IEC market. Test function and settings via micro USB port directly on the switch. Modular function groups always make mounting flexible and may be supplemented by the comprehensive range of accessories. R.m.s. value measurement and thermal memoryDelivery program

Product rangeCircuit-breakerProtective functionSystem and cable protectionStandard/ApprovalIECInstallation

typeFixedRelease systemElectronic releaseConstruction sizeNZM2DescriptionOverload and short-circuit protection LI R.m.s. value measurement and "thermal memory"

USB interface for configuration and test function with Power Xpert Protection Manager softwareNumber of poles4

poleStandard equipmentScrew connectionSwitching capacity400/415 V 50 Hz [Icu]70 kARated current = rated uninterrupted

current [ $I_n = I_u$ ] Rated current = rated uninterrupted current [ $I_n = I_u$ ] 25 A Neutral conductor [% of phase conductor] 100  
% Setting range Overload trip [ $I_r$ ] 20 - 25 A Short-circuit releases [ $I_{rm}$ ] Non-delayed [ $I_i = I_{nx} \dots$ ] 2 - 12 Technical data  
General Standards IEC/EN 60947 Protection against direct contact Finger and back of hand proof to VDE 0106 Part  
100 Climatic proofing Damp heat, constant, to IEC 60068-2-78  
Damp heat, cyclic, to IEC 60068-2-30 Ambient temperature Ambient temperature, storage-....

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / NZMS2-4-AX25 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use  
[electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd  
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification  
requirements against the manufacturer documentation before purchase or installation.