

INDUSTRIAL COMPONENT DATA

NZMS2-A200-SVE 113290 Y7-113290 EATON ELECTRIC

Circuit breaker 3-pole 200 A, system/cable protection, withdr..

Brand: EATON - MOELLER | Manufacturer Part Number: NZMS2-A200-SVE



Manufacturer	EATON - MOELLER
MPN / Reference	NZMS2-A200-SVE
Catalog number	Y7-113290
Category	Power circuit-breaker for trafo/generator/installation protection
Minimum order	1 Pcs
Document ID	EO-846005E738
Generated	2026-08-01

Product Overview

Circuit breaker 3-pole 200 A, system/cable protection, withdrawable unit

NZMS2-A200-SVE

Series NZM...-A circuit-breakers cover all application cases with just four compact sizes and are suitable for the IEC market. Modular function groups always make mounting flexible. With thermomagnetic releases for systems and cable protection.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Circuit Breakers NZM

Additional Product Information

Circuit breaker 3-pole 200A, system/cable protection, withdrawable unitSeries NZM...-A circuit-breakers cover all application cases with just four compact sizes and are suitable for the IEC market. Modular function groups always make mounting flexible. With thermomagnetic releases for systems and cable protection.

General specificationsProduct nameEaton Moeller series NZM molded case circuit breaker thermo-magneticPart no.NZMS2-A200-SVEEAN4015081128259Product Length/Depth180 millimetreProduct height245 millimetreProduct width105 millimetreProduct weight2.804 kilogramCompliancesRoHS conform

CE MarkedProduct TradenameNZMProduct TypeMolded case circuit breakerProduct Sub TypeThermo-magneticDelivery programNumber of polesThree-poleAmperage Rating200 AFeaturesMotor drive optional

Protection unitSpecial featuresRated current = rated uninterrupted current: 200 ATechnical Data - ElectricalVoltage rating690 V - 690 VInstantaneous current setting (Ii) - min1200 AInstantaneous current setting (Ii) - max2000 AOverload current setting (Ir) - min160 AOverload current setting (Ir) - max200 AShort delay current setting (Isd) - min0 AShort delay current setting (Isd) - max0 AShort-circuit release non-delayed setting - min6 AShort-circuit release non-delayed setting -

max10 ARated short-circuit breaking capacity Ics (IEC/EN 60947) at 400/415 V, 50/60 Hz70 kAElectrical connection type of
main circuitScrew connectionHandle typeRocker leverTechnical Data - MechanicalMounting MethodBuilt-in device...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / NZMS2-A200-SVE with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.