

INDUSTRIAL COMPONENT DATA

NZMS2-A250-SVE 113291 Y7-113291 EATON ELECTRIC

Circuit breaker 3-pole 250 A, system/cable protection, withdr..

Brand: EATON - MOELLER | Manufacturer Part Number: NZMS2-A250-SVE



Manufacturer	EATON - MOELLER
MPN / Reference	NZMS2-A250-SVE
Catalog number	Y7-113291
Category	Power circuit-breaker for trafo/generator/installation protection
Minimum order	1 Pcs
Document ID	EO-B6469E62BF
Generated	2026-08-01

Product Overview

Circuit breaker 3-pole 250 A, system/cable protection, withdrawable unit

NZMS2-A250-SVE

Series NZM...-A circuit-breakers cover all application cases with just four compact sizes and are suitable for the IEC market. Modular function groups always make mounting flexible. With thermomagnetic releases for systems and cable protection.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Circuit Breakers NZM

Additional Product Information

Circuit breaker 3-pole 250A, system/cable protection, withdrawable unitSeries NZM...-A circuit-breakers cover all application cases with just four compact sizes and are suitable for the IEC market. Modular function groups always make mounting flexible. With thermomagnetic releases for systems and cable protection.

General specificationsProduct nameEaton Moeller series NZM molded case circuit breaker thermo-magneticPart no.NZMS2-A250-SVEEAN4015081128266Product Length/Depth180 millimetreProduct height245 millimetreProduct width105 millimetreProduct weight2.81 kilogramCompliancesRoHS conformProduct TradenameNZMProduct TypeMolded case circuit breakerProduct Sub TypeThermo-magneticDelivery programNumber of polesThree-poleAmperage Rating250 AFeaturesMotor drive optional

Protection unitSpecial featuresRated current = rated uninterrupted current: 250 ATechnical Data - ElectricalVoltage rating690 V - 690 VInstantaneous current setting (Ii) - min1500 AInstantaneous current setting (Ii) - max2500 AOverload current setting (Ir) - min200 AOverload current setting (Ir) - max250 AShort delay current setting (Isd) - min0 AShort delay current setting (Isd) - max0 AShort-circuit release non-delayed setting - min6 AShort-circuit release non-delayed setting -

max10 ARated short-circuit breaking capacity Ics (IEC/EN 60947) at 400/415 V, 50/60 Hz70 kAElectrical connection type of
main circuitScrew connectionHandle typeRocker leverTechnical Data - MechanicalMounting MethodBuilt-in device plug-in
te...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / NZMS2-A250-SVE with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.