

INDUSTRIAL COMPONENT DATA

NZMS2-AX63 192029 EATON ELECTRIC Automatic int. NZM2 PXR10, 3p, 63A, screw terminal

Brand: EATON - MOELLER | Manufacturer Part Number: NZMS2-AX63



Manufacturer	EATON - MOELLER
MPN / Reference	NZMS2-AX63
Catalog number	192029
Category	Power circuit-breaker for trafo/generator/installation protection
Minimum order	1 Pcs
Document ID	EO-3DD6A1AF35
Generated	2026-08-04

Product Overview

Automatic int. NZM2 PXR10, 3p, 63A, screw terminal

Circuit-breaker, NZM2 PXR10, 3 pole, 63A, screw terminal

The xEffect NZM...-AX circuit breaker range with the power expert release (PXR) electronic triggering system covers use cases for system and cable protection with only four compact sizes and is suitable for the IEC market. Test function and settings via micro USB port directly on the switch. Modular function groups always make mounting flexible and may be supplemented by the comprehensive range of accessories. R.m.s. value measurement and thermal memory

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Circuit Breakers NZM

Additional Product Information

Circuit-breaker, NZM2 PXR10, 3 pole, 63A, screw terminalThe xEffect NZM...-AX circuit breaker range with the power expert release (PXR) electronic triggering system covers use cases for system and cable protection with only four compact sizes and is suitable for the IEC market. Test function and settings via micro USB port directly on the switch. Modular function groups always make mounting flexible and may be supplemented by the comprehensive range of accessories.

R.m.s. value measurement and thermal memoryDelivery program

Product rangeCircuit-breakerProtective functionSystem and cable protectionStandard/ApprovalIECInstallation

typeFixedRelease systemThermomagnetic releaseConstruction sizeNZM2DescriptionOverload and short-circuit protection LI

R.m.s. value measurement and "thermal memory"

USB interface for configuration and test function with Power Xpert Protection Manager softwareNumber of poles3

poleStandard equipmentScrew connectionSwitching capacity400/415 V 50 Hz [Icu]70 kARated current = rated uninterrupted current [In= Iu]Rated current = rated uninterrupted current [In= Iu]63 ASetting rangeOverload trip[Ir]50 - 100 AShort-circuit releases[Irm]Non-delayed[Ii= Inx ...]2 - 18Technical data
GeneralStandardsIEC/EN 60947Protection against direct contactFinger and back of hand proof to VDE 0106 Part 100Climatic proofingDamp heat, constant, to IEC 60068-2-78
Damp heat, cyclic, to IEC 60068-2-30Ambient temperatureAmbient temperature, storage- 40 - + 70 °CAmbient temperatureOper...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / NZMS2-AX63 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.