

INDUSTRIAL COMPONENT DATA

NZMS2-M125 109976 Y7-109976 EATON ELECTRIC NZM Auto Int., 3P, lu: 125A

Brand: EATON - MOELLER | Manufacturer Part Number: NZMS2-M125



Manufacturer	EATON - MOELLER
MPN / Reference	NZMS2-M125
Catalog number	Y7-109976
Category	Motor protection circuit-breaker
Minimum order	1 Pcs
Document ID	EO-B25D414F25
Generated	2026-08-02

Product Overview

NZM Auto Int., 3P, lu: 125A

NZMS2-M125

Circuit-breaker 3 pole, 125A, motor protection

Circuit-breakers of the NZM..-M series cover all applications with only four compact sizes and are suitable for the IEC market. The mounting is always flexible due to the modular function groups. With thermomagnetic release for the motor protection. Notes: tripping class 10A, IEC/EN 60947-4-1, IEC/EN 60947-2 circuit-breakers fulfill all requirements of the switching category AC-3.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Circuit Breakers NZM

Additional Product Information

Circuit-breaker 3 pole, 125A, motor protectionCircuit-breakers of the NZM..-M series cover all applications with only four compact sizes and are suitable for the IEC market. The mounting is always flexible due to the modular function groups. With thermomagnetic release for the motor protection. Notes: tripping class 10A, IEC/EN 60947-4-1, IEC/EN 60947-2 circuit-breakers fulfill all requirements of the switching category AC-3.

General specificationsProduct nameEaton Moeller series NZM - Molded Case Circuit BreakerPart no.NZMS2-M125EAN4015081095421Product Length/Depth149 millimetreProduct height184 millimetreProduct width105 millimetreProduct weight2.334 kilogramCompliancesRoHS conformProduct TradenameNZMProduct TypeMolded Case Circuit BreakerProduct Sub TypeNoneDelivery programNumber of polesThree-poleAmperage Rating125 ASpecial featuresIEC/EN 60947-4-1, IEC/EN 60947-2The circuit-breaker fulfills all requirements for AC-3 switching category.Rated

current = rated uninterrupted current: 125 A Tripping class 10 A Technical Data - Electrical Voltage rating 690 V - 690 V Rated operational current 100 A (400 V AC-3) Instantaneous current setting (Ii) - min 1000 A Instantaneous current setting (Ii) - max 1750 A Overload current setting (Ir) - min 100 A Overload current setting (Ir) - max 125 A Short-circuit release non-delayed setting - min 1000 A Short-circuit release non-delayed setting - max 1750 A Rated short-circuit breaking capacity Ics (IEC/EN 60947) at 400/415 V, 50/60 Hz 150 kA Rated operating....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / NZMS2-M125 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.