

INDUSTRIAL COMPONENT DATA

NZMS2-M125-SVE 113301 Y7-113301 EATON ELECTRIC

Circuit-breaker 3-pole 125 A, motor protection, withdrawable ..

Brand: EATON - MOELLER | Manufacturer Part Number: NZMS2-M125-SVE



Manufacturer	EATON - MOELLER
MPN / Reference	NZMS2-M125-SVE
Catalog number	Y7-113301
Category	Motor protection circuit-breaker
Minimum order	1 Pcs
Document ID	EO-B6975F04FB
Generated	2026-08-04

Product Overview

Circuit-breaker 3-pole 125 A, motor protection, withdrawable unit

NZMS2-M125-SVE

Circuit-breakers of the NZM...M series cover all applications with only four compact sizes and are suitable for the IEC market. The mounting is always flexible due to the modular function groups. With thermomagnetic release for the motor protection. Notes: tripping class 10A, IEC/EN 60947-4-1, IEC/EN 60947-2 circuit-breakers fulfill all requirements of the switching category AC-3.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Circuit Breakers NZM
--------------	--

Additional Product Information

Circuit-breaker 3-pole 125A, motor protection, withdrawable unitCircuit-breakers of the NZM...M series cover all applications with only four compact sizes and are suitable for the IEC market. The mounting is always flexible due to the modular function groups. With thermomagnetic release for the motor protection. Notes: tripping class 10A, IEC/EN 60947-4-1, IEC/EN 60947-2 circuit-breakers fulfill all requirements of the switching category AC-3.

General specificationsProduct nameEaton Moeller series NZM molded case circuit breaker thermo-magneticPart no.NZMS2-M125-SVEEAN4015081128365Product Length/Depth180 millimetreProduct height245 millimetreProduct width105 millimetreProduct weight2.774 kilogramCompliancesRoHS conformProduct TradenameNZMProduct TypeMolded case circuit breakerProduct Sub TypeThermo-magneticDelivery programNumber of polesThree-poleAmperage Rating125 ASpecial featuresRated current = rated uninterrupted current: 125 ATripping class 10 AIEC/EN 60947-4-1, IEC/EN 60947-2The circuit-breaker fulfills all requirements for AC-3 switching category.Technical Data - ElectricalVoltage rating690

V - 690 V Rated operational current 100 A (400 V AC-3) Instantaneous current setting (Ii) - min 100 A Instantaneous current setting (Ii) - max 1750 A Overload current setting (Ir) - min 100 A Overload current setting (Ir) - max 125 A Short-circuit release non-delayed setting - min 1000 A Short-circuit release non-delayed setting - max 1750 A Rated short-circuit breaking capacity Ics (IEC/EN 6094...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / NZMS2-M125-SVE with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.