

INDUSTRIAL COMPONENT DATA

NZMS2-M25-SVE 113294 EATON ELECTRIC Circuit-breaker 3-pole 25 A, motor protection, withdrawable unit

Brand: EATON - MOELLER | Manufacturer Part Number: NZMS2-M25-SVE



Manufacturer	EATON - MOELLER
MPN / Reference	NZMS2-M25-SVE
Catalog number	113294
Category	Motor protection circuit-breaker
Minimum order	1 Pcs
Document ID	EO-2EFD45164A
Generated	2026-08-04

Product Overview

Circuit-breaker 3-pole 25 A, motor protection, withdrawable unit

Circuit-breakers of the NZM...-M series cover all applications with only four compact sizes and are suitable for the IEC market. The mounting is always flexible due to the modular function groups. With thermomagnetic release for the motor protection. Notes: tripping class 10A, IEC/EN 60947-4-1, IEC/EN 60947-2 circuit-breakers fulfill all requirements of the switching category AC-3.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Circuit Breakers NZM

Additional Product Information

Circuit-breaker 3-pole 25 A, motor protection, withdrawable unit Circuit-breakers of the NZM...-M series cover all applications with only four compact sizes and are suitable for the IEC market. The mounting is always flexible due to the modular function groups. With thermomagnetic release for the motor protection. Notes: tripping class 10A, IEC/EN 60947-4-1, IEC/EN 60947-2 circuit-breakers fulfill all requirements of the switching category AC-3. [Delivery program

Description Tripping class 10 A

IEC/EN 60947-4-1, IEC/EN 60947-2

The circuit-breaker fulfills all requirements for AC-3 switching category.

Switching capacity 400/415 V 50 Hz [Icu] 70 kA Rated current = rated uninterrupted current [In= Iu] 25 A Setting range

Overload trip[I_r] 20 - 25 A Short-circuit releases [I_{rm}]Non-delayed [I_i= I_{nx} ...] 350 A fixed Motor rating AC-3 50/60 Hz [P] 380 V 400 V [P] 11 kW Motor rating AC-3 50/60 Hz [P] 400 V [P] 11 kW Rated operational current AC-3 50/60 Hz [I_e] 400 V [I_e] 21.7 A , Technical data

General Ambient temperature Ambient temperature, storage - 40 - + 70 °C Ambient temperature Operation -25 - +70 °C
Circuit-breakers Rated current = rated uninterrupted current [In= Iu] 25 A Switching capacity Rated short-circuit breaking capacity Icn[Icn]Icu to IEC/EN 60947 test cycle O-t-CO [Icu]400/415 V 50/60 Hz [Icu] 70 kA , Design verification as per IEC/EN 61439

Technical data for design verification Equipment heat dissipation, current-dependent [Pvid] 7.97 W Operating ambient temperature mi...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / NZMS2-M25-SVE with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.