

INDUSTRIAL COMPONENT DATA

NZMS2-M63-SVE 113298 Y7-113298 EATON ELECTRIC

Circuit-breaker 3-pole 63 A, motor protection, withdrawable un..

Brand: EATON - MOELLER | Manufacturer Part Number: NZMS2-M63-SVE



Manufacturer	EATON - MOELLER
MPN / Reference	NZMS2-M63-SVE
Catalog number	Y7-113298
Category	Motor protection circuit-breaker
Minimum order	1 Pcs
Document ID	EO-C132214063
Generated	2026-08-04

Product Overview

Circuit-breaker 3-pole 63 A, motor protection, withdrawable unit

NZMS2-M63-SVE

Circuit-breakers of the NZM...-M series cover all applications with only four compact sizes and are suitable for the IEC market. The mounting is always flexible due to the modular function groups. With thermomagnetic release for the motor protection. Notes: tripping class 10A, IEC/EN 60947-4-1, IEC/EN 60947-2 circuit-breakers fulfill all requirements of the switching category AC-3.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Circuit Breakers NZM

Additional Product Information

Circuit-breaker 3-pole 63A, motor protection, withdrawable unitCircuit-breakers of the NZM...-M series cover all applications with only four compact sizes and are suitable for the IEC market. The mounting is always flexible due to the modular function groups. With thermomagnetic release for the motor protection. Notes: tripping class 10A, IEC/EN 60947-4-1, IEC/EN 60947-2 circuit-breakers fulfill all requirements of the switching category AC-3.

General specificationsProduct nameEaton Moeller series NZM molded case circuit breaker thermo-magneticPart no.NZMS2-M63-SVEEAN4015081128334Product Length/Depth180 millimetreProduct height245 millimetreProduct width105 millimetreProduct weight2.798 kilogramCompliancesRoHS conformProduct TradenameNZMProduct TypeMolded case circuit breakerProduct Sub TypeThermo-magneticDelivery programNumber of polesThree-poleAmperage Rating63

ASpecial featuresRated current = rated uninterrupted current: 63 ATripping class 10 AIEC/EN 60947-4-1, IEC/EN 60947-2The circuit-breaker fulfills all requirements for AC-3 switching category.Technical Data - ElectricalVoltage rating690 V - 690 VRated operational current55 A (400 V AC-3)Instantaneous current setting (Ii) - min504 AInstantaneous current setting (Ii) - max882 AOverload current setting (Ir) - min50 AOverload current setting (Ir) - max63 AShort-circuit release non-delayed setting - min504 AShort-circuit release non-delayed setting - max882 ARated short-circuit breaking capacity Ics (IEC/EN 60947) at 400/4...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / NZMS2-M63-SVE with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.